

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. Contract No. 42
2. NAME OF OPERATOR Continental Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla Apache
3. ADDRESS OF OPERATOR 152 North Durbin, Casper, Wyoming 82601		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 990' FNL, 990' FWL New Mexico Letter "D"		8. FARM OR LEASE NAME AXI Apache "D"
14. PERMIT NO.		9. WELL NO. 3
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6730' GR, 6759' DF		10. FIELD AND POOL, OR WILDCAT Ballard Pictured Cliffs
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 20, T24N, R4W
		12. COUNTY OR PARISH Rio Arriba
		13. STATE New Mexico

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

This well was drilled to a total depth of 2730'. 9 5/8" OD, 36#, J-55 surface casing was set and cemented with 85 sacks of cement. 3 1/2" OD, 7.7#, J-55 casing was set at 2713' with 200 sacks of cement. The well was completed in the Pictured Cliffs with perforations from 2617-22' and 2647-56' with 2 jets per foot.

We are proposing to plug and abandon this well by placing a 10 sack cement plug at 2636' RBM. A 15 sack cement plug will be placed across the Ojo Alamo formation inside the 3 1/2" OD casing at approximately 2154' RBM. The 3 1/2" OD casing will be cut and pulled at approximately 173' RBM and a 20 sack cement plug will be placed across the top of the surface casing. All intervals between the cement plugs will be filled with a heavy drilling mud. A regulation P&A marker will be installed and the location will be restored to its natural condition.

USGS(4) NMOCC(2) EXXON Co. File(2)

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Division Manager

DATE

2-26-73

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

U.S. GEOLOGICAL SURVEY