Form 9-331 (May 1963)

## UNITED STATES

SUBMIT IN TRIPLICATE.

Form approved.

DEPARTMENT OF THE INTERIOR (Other Instructions on re-				5. LEASE DESIGNATION AND SERIAL NO. New Mexico 0338445
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)				6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL X GAS OTHER				7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR				8. FARM OR LEASE NAME
J. J. August and R. D. Sawyer				Mobil - Federal
3. ADDRESS OF OPERATOR				9. WELL NO.
1736 Westwood Blvd., Los Angeles, California 90024				#1 *** #1 *** *** *** *** *** *** *** **
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface				10. FIELD AND POOL, OR WILDCAT Wildcat
1980' FSL and 1980' FEL Sec. 36. T.24 N., R. 1 W.,				11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
1d punkty No		15. ELEVATIONS (Show whether DF, RT, GR, etc.)		Sec 36: T.24N., R.1W.,
14. PERMIT NO.		7200' (Ground		Rio Arriba New Mexico
		7200 (Ground	<u>/</u>	1 110 ATTIDA   New Mexico
16. Check Appropriate Box To Indicate Nature of Notice, Repo			SUBSEQU	ENT REPORT OF:
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF				REPAIRING WELL,
FRACTURE TREAT  MULTIPLE COMPLETE  FRACTURE TREATMENT  SHOOT OR ACIDIZE  ABANDON*  SHOOTING OR ACIDIZING				ABANDONMENT*
SHOOT OR ACIDIZE  REPAIR WELL  CHANGE PLANS  (Other)				
	n Surface Casi	!	(Note: Report results	of multiple completion on Well etion Report and Log form.)
17. DESCRIBE PROP	OSED OR COMPLETED OFE ork. If well is direction	RATIONS (Clearly state all pertinent	details, and give pertinent dates.	including estimated date of starting any il depths for all markers and zones perti-
		k, Licensed Surveyor ection 36, T. 24 N., 1		e, staked location 1980' FSL riba County.
9-1 <b>-</b> 64 War	ren Howard, Gr	aded roads installed	3 culverts and grade	ed location site.
	Earl Densmore, Grants, New Mexico moved in portable rotary rig, spudded at 1:30 PM. drilling 13 $3/4\frac{1}{4}$ hole in shale surface to 55 ft.			
97.		hole 55' to 101 ft. , seamless casing wi	Blackman Cementing th 90 sax. Good retu	
			RECEIVE	5 ( DOT 1 3 284)

OCT 15 1964

U. S. GEOLOGICAL SURVEY FLEMINGTON, N. D.