

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
SF 079177

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☐ GAS ☒ WELL ☐ OTHER

2. NAME OF OPERATOR
Merrion & Bayless

3. ADDRESS OF OPERATOR
Box 1541 Farmington, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
1820' FSL & 810' FEL 9-25-6

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Canyon Largo

8. FARM OR LEASE NAME

Hill

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesig Chacra

11. SEC. T. R. M. OR BLK. AND
SURVEY OR AREA.

9-25-6

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6534 g1

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mex

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) cementing casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 9-7/8" hole and set 102' of 7-5/8" casing w/ 50 sax cement
Drilled 6-3/4" hole to 3607' KB and set 3628' (115 jts) of 2-1/2" EUE
casing @ 3606' w/ float collar @ 3588' w/ 250 sax cement 50-50 pozmix,
displaced plug w/ 250 gallons 10% acetic acid followed by water.
Temperature survey showed top cement @ 2450'

18. I hereby certify that the foregoing is true and correct

SIGNED

B. L. Bayless

TITLE

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE Oct 16, 1966

DATE

