	-		
l	.		
		-	
l	.i		
	· ļ		
1	1		
i	i	:	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

E A Land Offic	pprove	Bureau No. 42 al expires 12–31 San t	-60.
Land Um			
	SF	079325	-A
Lease No.			
		H	
Unit			

GPO 918507

NOTICE OF INTENTION TO DRILL.		SUBSEQUENT REPORT O	F WATER SHUT-OFF	· · · · · · · · · · · · · · · · · · ·
NOTICE OF INTENTION TO CHANGE	I		F SHOOTING OR ACIDIZII	NG
NOTICE OF INTENTION TO TEST W	ATER SHUT-OFF	SUBSEQUENT REPORT O	F ALTERING CASING	<u>. 8 - 14 30</u>
NOTICE OF INTENTION TO RE-DRII	LL OR REPAIR WELL	SUBSEQUENT REPORT O	F RE-DRILLING OR REPA	ir. 134 704
NOTICE OF INTENTION TO SHOOT	OR ACIDIZE	SUBSEQUENT REPORT O	F ABANDONMENT	
NOTICE OF INTENTION TO PULL O	R ALTER CASING	SUPPLEMENTARY WELL	HISTORY	
NOTICE OF INTENTION TO ABANDO	ON WELL			
(iNDI	CATE ABOVE BY CHECK MARK NA	TURE OF REPORT, NOTICE, (OR OTHER DATA)	
`		Sept 21 19)60	
oyal K ern #1	•		-	,
	1980	(N) 660	(F.)	. 3
	ated tt. from	$\left\{ egin{array}{c} \mathbf{N} \\ \mathbf{S} \end{array} \right\}$ line and	. It. from \mathbb{W} line	e of sec
BE HE Sec 3	25N 1E	NAPA	()	
Unit Sec. Ind Sec. No.)	Rib ^p Arriba ^{(Ra}	ange) (Me	ridian)	
(Field)	(County or Su		(State or Territ	
	(Country of St	20017131011)	(Digito of Tellin	or y)
The elevation of the derric	ck floor above sea level	70 52 ft. Grou	ind Level	
The elevation of the derric	ck floor above sea level DETAILS	7052 ft. Grou		mudding iobs.
The elevation of the derric	ck floor above sea level	7052 ft. Grou	posed casings; indicate a	mudding jobs, P lu<i>ces</i>
The elevation of the derrice (State names of and expected depth ling, Set 40 7	DETAILS to objective sands; show sizes, OD UTIVE CERENT 55 10 sex. Par	70 52 ft. S OF WORK weights, and lengths of pro imperiant proposed work A 32 deg 1	posed casings; indicate:	Plugge
The elevation of the derrice (State names of and expected depth 11 10 N. Set 128 5 122 5 128 122 5 128 128 122 5 128	DETAILS to objective sands; show sizes, OD UING TEMENT 58 10 sax. Par	70 52 IS ft. S OF WORK weights, and lengths of pro important proposed work Wild stoppe 432 deg 1	posed casings; indicates d Drilling. eg. Plg w/6	Plugge Sax31
The elevation of the derrice (State names of and expected depth 110	DETAILS TO Objective sands; show sizes, very complete to sands; show sizes, very complete to the complete to	7052 ft. FOR WORK Weights, and lengths of program proposed work Weights, and lengths of program proposed work Wild Ecoppe 432 deg 1 111ed to 195	d Drilling. eg. Plg w/6 . Water = 1	Plugge /sax2} 50'. At
The elevation of the derrice (State names of and expected depth Ling. Set 40 7 1 10 N. Set 128 5 122 5 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	DETAILS to objective sands; show sizes, very complete to example to the complete to the compl	7052 ft. S OF WORK weights, and lengths of pro important proposed work A 32 dog 1 illed to 195 and turned ho Drilled 4-3	posed casings; indicates d Drilling. eg. Plg w/6 . Water = 1 le over to /4 hole wit	Plugge /sat2) 50'. Ab UB Fore
The elevation of the derrice (State names of and expected depth) 10 N. Set 128 5 10 N. Set 122 5 10 N. Set 167 8-5/8 1888 Plugged	DETAILS to objective sands; show sizes, to DETAILS 10 cax. Palling 20/Sex. Driveral approval approval approval sto surface.	7052 ft. S OF WORK weights, and lengths of pro- improved work 432 dog 1 liled to 195 and turned ho Drilled 4-3 with 75 sax	d Drilling. d Drilling. eg. Plg w/6 . Water = 1 le over to /4 hole with	Plugge /sat2H 50'. Al US Fore h air t
The elevation of the derricular of the derricula	DETAILS to objective sands; show sizes, to objective sands; show sands	7052 ft. S OF WORK weights, and lengths of pro- improved work 432 dog 1 liled to 195 and turned ho Drilled 4-3 with 75 sax to set appro-	d Drilling. d Drilling. eg. Plg w/6 . Water = 1 le over to /4 hole with by Hallibur x 1200 2-7	Plugge /sat2H 50'. Al US Fore h air t
The elevation of the derrice (State names of and expected depth) 10 N. Set 128 5 10 N. Set 122 5 10 N. Set 167 8-5/8 1888 Plugged	DETAILS to objective sands; show sizes, to objective sands; show sands	7052 ft. S OF WORK weights, and lengths of pro- improved work 432 dog 1 liled to 195 and turned ho Drilled 4-3 with 75 sax to set appro-	d Drilling. d Drilling. eg. Plg w/6 . Water = 1 le over to /4 hole with by Hallibur x 1200 2-7	Plugge /sat2H 50'. Al US Fore h air t
The elevation of the derricular of the derricula	DETAILS to objective sands; show sizes, to objective sands; show sands	7052 ft. S OF WORK weights, and lengths of pro- improved work 432 dog 1 liled to 195 and turned ho Drilled 4-3 with 75 sax to set appro-	d Drilling. d Drilling. eg. Plg w/6 . Water = 1 le over to /4 hole with by Hallibur x 1200 2-7	Plugge /sat2H 50'. Al US Fore h air t
The elevation of the derricular of the derricula	DETAILS to objective sands; show sizes, to objective sands; show sands	7052 ft. S OF WORK weights, and lengths of pro- improved work 432 dog 1 liled to 195 and turned ho Drilled 4-3 with 75 sax to set appro-	d Drilling. d Drilling. eg. Plg w/6 . Water = 1 le over to /4 hole with by Hallibur x 1200 2-7	Plugge /sat2H 50'. Al US Fore h air t
The elevation of the derricular of the derricula	DETAILS to objective sands; show sizes, to objective sands; show sands	7052 ft. S OF WORK weights, and lengths of pro- improved work 432 dog 1 liled to 195 and turned ho Drilled 4-3 with 75 sax to set appro-	d Drilling. d Drilling. eg. Plg w/6 . Water = 1 le over to /4 hole with by Hallibur x 1200 2-7	Plugge /sat2H 50'. Al US Fore h air t
The elevation of the derricular of the derricula	DETAILS to objective sands; show sizes, to objective sands; show sands	7052 ft. S OF WORK weights, and lengths of pro- improved work 432 dog 1 liled to 195 and turned ho Drilled 4-3 with 75 sax to set appro-	d Drilling. d Drilling. eg. Plg w/6 . Water = 1 le over to /4 hole with by Hallibur x 1200 2-7	Plugge /sat2H 50'. Al US Fore h air t
The elevation of the derricular of the derricula	DETAILS To objective sands; show sizes, OD 'U'I''' Callent St 10 sax. Par Dire 20/Bax. Dri Trbal approval Cem to surface. I back to 1200' otion. Intend Llup formation;	7052 ft. S OF WORK weights, and lengths of pro- important proposed work 432 deg 1 illed to 195 and turned ho Drilled 4-3 with 75 sax to set appro-	posed casings; indicates at Drilling. og. Plg w/6. Water of 1 to over to 1 to hele with by Hellibur's 1200' 2-7, at free. REFERENCE SEP 23 19	Plugge /sat3): 50'. At US Fore h air t ton. Oi /8" Cas
The elevation of the derricular of the derricular of and expected depth ling. Set 40 71 10 N. Set 128 S: set 122 52 Cring with USGS versions with USGS versions for complete to protect (a) I understand that this plan of we Reyal Deve	DETAILS To objective sands; show sizes, OD 'UTW' Callent St 10 sax. Par Dire 20/Bax. Dri Trbal approval Cem to surface. I back to 1200' Stion. Intend Lup formation;	7052 ft. S OF WORK weights, and lengths of pro- important proposed work 432 deg 1 illed to 195 and turned ho Drilled 4-3 with 75 sax to set appro-	posed casings; indicates at Drilling. eg. Plg w/6, leg. Plg w/6, water a l leg. Plg w/6, leg. Plg w	Plugge /sat3): 50'. At US Fore h air t ton. Oi /8" Cas
The elevation of the derricular of the derricular of and expected depth ling. Set 40 71 10 N. Set 128 S; set 122 52 Cring with USGS very 1888 Plugged Crools for complement to protect delivation of we recommend that this plan of we company	DETAILS To objective sands; show sizes, OD 'U'I''' Callent St 10 sax. Par Dire 20/Bax. Dri Trbal approval Cem to surface. I back to 1200' otion. Intend Llup formation;	7052 ft. S OF WORK weights, and lengths of pro- important proposed work 432 deg 1 illed to 195 and turned ho Drilled 4-3 with 75 sax to set appro-	posed casings; indicates a Drilling. eg. Plg w/6 . Water 3 1 le over to /4 hole with by Hallibur x 1200' 2-7 d frag. REFERE	Plugge /sat3): 50'. At US Fore h air t ton. Oi /8" Cas
The elevation of the derricular of the derricular of and expected depth ling. Set 40 7 1 10 N. Set 128 S: set 122 5 1 (25 mg with USGS versions with USGS versions 1888 Plugged Crools for complement to protect (a)	DETAILS To objective sands; show sizes, OD 'UTW' Callent St 10 sax. Par Dire 20/Bax. Dri Trbal approval Cem to surface. I back to 1200' Stion. Intend Lup formation;	7052 ft. S OF WORK weights, and lengths of pro- important proposed work 432 deg 1 illed to 195 and turned ho Drilled 4-3 with 75 sax to set appro-	posed casings; indicates at Drilling. eg. Plg w/6, leg. Plg w/6, water a l leg. Plg w/6, leg. Plg w	Plugge /sat3): 50'. At US Fore h air t ton. Oi /8" Cas



4...