This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

	* * • • • •		I MEN PER				Well _
perator	Continent	al Oil Compe	any	Lea	se	arilla 28	No5
ocation	+ J Soc	33 Than	OSM	Pæs	ler	County	z Bio Amelho
well: Uni	.tsec	33 IMD.	Two c	nge.	Mot had	of Prod	Rio Arriba Prod. Medium
	Name of Reser	moir or Poo	Type C	n Gael	(Flow or	Art. Lift)	(Tbg. or Csg.)
per	Name of Reser	VOII OI 100	1 (011 6	or das/	(FIOW OI	Arts Dirty	(10g. 01 Osg.)
mpletion	Gallup	•		11	T	low	Casing
wer	<u> </u>				<u>.</u>	70"	Cas TIR
mpletion	Dakota		1 6	11	1E)	low	Tubing
mpreoron	20000	PRE	FION SHIP	TN PRES	SIDE DATA		1 AVVAIR
per Hour, d	ate 11:00 A	M Lengt	h of hut-in h of		SI pres	SS.	Stabilized?
	in 8-7-70	time s	hut-in	72 Hrs.	psig	776	(Yes or No) No
	ate 11:00 A	M Lengt	h of		SI pres	33.	Stabilized?
mpl Shut-	in 8-7-70	time s	riiir 1 ri	12 HTS.	. 1 0519	685	(Yes or No) No
			LA' I I MAI	1111 211 1111			
menced at	(hour, date)	11:00	AM 8-10-7	0	Zone pr	oducing (Uppe	er or Lower): Low
Time	Lapsed time	Pr	essure	P	rod. Zone		_
our date)	since*	Upper Compl	Lower (compl.	Temp.	Rer	marks
1:00 AM		500			1		.
-7-70	-	500		500		At Time of	Shut-In
1:00 AM		FOF				ob **	
3-3-70 1:00 AM	 	5 85		555		24 Hrs. Aft	er snut-In
::••• AM }=9-70	_	625		6 0 5)12 True 1.01	an Church To
3:00 PM	 	635		·~/		48 Hrs. Aft	ET. DIMP-III
3 -10-7 0	4 Hrs.	7 80		100			
11:00 AM		L					
3-11-70	24 Hrs.	7 88		3 0			
per Hour, d		Lengt	MID-TEST SHUT-IN PRES Length of time shut-in		SI press.		Stabilized? (Yes or No)
ompl Shut-in ower Hour, date			Length of		psig SI press.		Stabilized?
mpl Shut-			hut-in		psig		(Yes or No)
p				TEST NO.			
mmenced at	(hour, date)	(*			Zone pr	roducing (Uppe	er or Lower):
Time	Lapsed time	Pr			rod. Zone		
our, date)	since **	Upper Compl	• Lower (Compl.	Temp.	Rei	marks
	ŀ						
	 						
					1,000		
				· · · · · · · · · · · · · · · · · · ·			
				÷			
	 						A STATE OF THE STA
	1			,	ļ	/_	000
							S59 15 60
	<u> </u>			·			an contin
			-	<u> </u>			OIL CON. COM
	<u> </u>	<u> </u>		· · · · · · · · · · · · · · · · · · ·			DIST. 3
oduction ra	te during tes	5t	mi. T	ام ئے۔ ام	Live	Conner	COB
<u> </u>	BOLD ps	MCEDD m	80.	la. III Drifica a	nrs.	arav.	GOR
5:		Trorro; Test	en outer (01 TI TOO O	- 1100e1 / i		
MARKS.							
marciae .	· · · · · · · · · · · · · · · · · · ·						
hereby cert	ify that the	information	herein co	ontained	is true an	nd complete to	the best of my
owledge.	•						*
	11		• • •	Operator		CONTINUENTAL O	
proved:	Oil Conservat:	<u> / ノ _ 19 /</u>	<u>(C</u>		1	ut D.a	1 A.
				Ву	roce	un N.C	Juson
13	12230	en San		m 2 1 3		Adminiates-i-	a Cumametera
	1/11/2/6	1111111	4_	TITTE		Administrativ	- Orber ATPOL
+1. אינייניינית רו	EUM ENGINEËF	DIST. NO. 3.		Date.	9	9-8-70	
THE PERKUL		, · · ·				,	

- 1. A packer leakage test shall be commenced on each sultiply completed well within seven days after actua, completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion Such tests shall also be commenced on all multiple confletions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packe or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Commission.
- At least 72 hours prior to the commencement of any packer leakage test the operator shall notify the Commission in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both rones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-bead pressure in each has stabilized, provided however, that they need not remain shut-in more than beyon days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shall-wh. Such test shall be continued for seven days in the case of a gas sent and for 24 hours in the case of an one well. Note: If, n. an intilligation leakage test, a gas well is being flowed to the arabb here due to the lock of a pipeline connection the flow period shall be the electric.
- Following completion of Flow lest No. 1, the well state again to state in accordance with Paragraph (above.
- 6. Flow Test No. 2 shall be condicted even though in less was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the provincesh produced zone shall remain shuttin while the zone which was previously shattin is produced.

- deadwoight pressure gauge at time intervals as follows: 3-hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the conclusion of each flow period, at least one time during each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test shall be continuously measured and recorded with recording pressure gauges, the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures a regulared above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 10 days after completion of the test. Tests shall be filed with the Azles Dairnic Offlice of the New Mexico Oil Conservation Commission on Spirickest New Mexico Packer Leakage Test Form Revised II-1-58, with all deadweight pressures indicated thereon as well as the flowing temperatures and zones only and gravity and GOR (oil zones only). A pressure versus time curve for each zone of each test shall be constructed on the reverse side of the Packer leakage Test Form with all deadweight pressure points taken indicated thereon. For oil zones, the pressure curve should also indicate all key pressure changes which may be reflected by the recording gauge charts. These key pressure changes should also be tabulated on the roch oil the Packer Leakage Test form.

