STATE OF NEW MEXICO

OIL CONSERVATION DIVISION

Page 1770 Page 1

This form is not to be used for reporting packer leakage tools

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

• •						
		•	W	7717		
Oneston Southern Union Exploration	n Lease	Jicarilla	No	o. <u>K14</u>		
Optiator			C	lio Arriba		
Location of Well: Unit 0 Sec. 11 Twp. 25	Rge	5	County _Rio Arriba			
	TYPE OF P	100.	THOD OF PROD.	(1bg. or Csg.)		
NAME OF RESERVOIR OR FOOL	(Oll or de		::	Csg. · ·		
South Blanco Pictured Cliff	Gas		Flow	Tbg		
Middle Otero Chacra	Gas					
Long	Gas		Flow	Tbg.		
Dasin Baroca	LOW SHUT-IN P	RESSURE DATA	• • •			
		lat nata		Yes.		
Upper 10/18/89 5	Days	VS		Yes		
Middle 19422189	Days	2. 31 / / 130		Yes		
	Days .	360 Yes				
	FLOW TEST	NO I				
	HOW IEST	Zone producing (Up)	ner or Lower):			
Commenced at fliour, date):*	ESSUNE					
TIME LAPSED TIME	He - Lower ^	PROD. ZONE		NEMANKS		
thour, detail SINCE* UPPET TIME	1/		· ·			
10/23/89 1 Day 356 15	0, 360	-				
10,100						
10/24/89 2 Days 356 15	0! 360	-	Well logged	off when it went		
256 15	360		on. Operato	or cleaned well		
10/25/89 J Days J Days			10/25/89	The same and a second particles of the same and the same a		
10/26/89 4 Days 356 29	5' 360					
	260		•			
10/27/89 5 Days 356 27	70 360	-				
				- Tall 7		
				Carlo Fred As		
Production rate during test				Ulsi. a		
	Dbls.	in Hour	Gtav	GOR		
Oil: BOPD based on	. Duis.					
M.	CEPD: Tested thi	u (Orillice or Mete	i):			
UA)		• •				
MID	TEST SHUT-IN	PRESSURE DATA	· Islahiii	ized? (Yes or No)		
Hous, date shut in Length of time	strut-in .	21 bisasi bain	:	· · · · · · · · · · · · · · · · · · ·		
Upp#f			Stabili	ized? (res of Ho)		
illour, date shul in Length of time	ahut In	Si press. pelg				
Compisition		<u> </u>				

REMARKS

FLOW TEST NO. 2

Lower Completion

PRESSURE

Upper Completion

Zone producing (Upper or Lower):

PROD. ZONE

TEMP.

		7084 hibror	PAGEORY S	1447 8 94807 34	Mariancon	A CANADA
		, ·		. :		
	· · · · · · · · · · · · · · · · · · ·		rangerar at the		1	
		. 1 - 24.25				the state of the s
1 •:			e j			· · · ·
The many of the second			grandi ang at maran			
		D based on	Bbls. in		Grav	v GOR
Remarks:			e aporte y constant con træst	5 am 15556 - 10 - 1 - 1 - 1 - 4 - 4 - 4 - 10 - 10		and the second s
I hereby certify th	nat the informati		ed is true and co	mplete to the bes		dge.
:	il Conservation I	Division	•		hern Union	Exploration
Ву	ned by CHARLES	Sinces	Т	itle Tecl	nician	
Title DEPUTY	OIL & GAS INSPE	CTOR, DIST. #3	· ! I	Date11/1	4/89	
İ					:	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Commenced at (hour, date)**

LAPSED TIME

SINCE **

TIME

(hour, date)

- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut in for pressure stabilization. Both zones shall remain shut in until the well-head pressure in each has stabilized, provided however, that they need not remain shut in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall temain shur-in while the zone which was previously shur-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).