

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)Form approved  
Budget Bureau No. 42-R1424.  
5. LEASE DESIGNATION AND SERIAL NO.

65

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla 22

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

W. Lindrith - Undesignated Gallup and Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 22, T25N, R4W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐  
2. NAME OF OPERATOR

Continental Oil Company

3. ADDRESS OF OPERATOR

152 North Durbin St., Casper, Wyo. 82601

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

NW SW 790' FWL, 1870' FSL (Unit Letter "L")

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7001.0' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Casing Run

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)


17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

This well was spudded on September 23, 1971. Drilled 12 1/4" hole to 242' RB and ran seven joints 8 5/8" OD, 24#, K-55, ST&C casing set at 239' RB and cemented w/150 sacks of Class "A" cement w/2% KCl.

Drilled 7 7/8" hole to 7820' total depth. Ran FDC-GR 7813-6500', 5700-6000', and 4409-4200'; Caliper from 7813-7100'. Log Tops:

Chacra 4243'  
Mesa Verde 5045'  
Gallup 6685'

Graneros 7478'  
Dakota 7558'



Ran Baker guide shoe, one 11.6#, N-80 shoe joint, Model "G" differential fill collar and Baker stage collar 5810'. Cement basket at 5844'. Ran 232 joints of 4 1/2" OD, 10.5#, K-55, ST&C casing and four joints of 10.5#, N-80, LT&C casing landed at 7820' RB. Dowell cemented first stage w/380 sacks 50-50 "Lite-Poz" w/2% D-20, 1/2% D-65, and 6 1/4#/sack D-42.

(Continued next page)

USGS(5) File(2)

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Administrative Supervisor

DATE 1/25/72

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side

U. S.