Form	9331
(May	1963)

## UNITED STATES DEPARTMENT OF THE INTERIOR

SUBMIT (Other i verse side	IN	TRIPL	ICA:	re•
(Other 4	nstr	uctions	on	re-
cerse side				

Form appr	ok	ed.					
Form appr Budget Bu	ŋe:	H	N	0.	42	-R	142
LEASE DESIGNATION	×	3.5	Ü	81	CRI.	Al.	NO.

	GE	COLOGICAL SURVEY		SF 078885	
SUN (Do not use this	DRY NOTION OF THE PROPERTY OF	ES AND REPORTS ( s to drill or to deepen or plug   10N FOR PERMIT—" for such p	ON WELLS back to a different reservoir. proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
I.				7. UNIT AGREEMENT NAME	
OIL GAS WELL	X OTHER			Canyon Largo Unit	
2. NAME OF OPERATOR El Paso Natu	ral Gas Cor	npany		8. FARM OR LEASE NAME Canyon Largo Unit	
3. ADDRESS OF CPERATOR PO Box 990,	Farmington	, NM 87401	g 1972	9. WELL NO. 177	
4. LIGCATION OF WELL (1 See also space 17 bel At surface	t-port location cle ow.)	arly and in accordance with an 1500'N,	900'W CON. CO'	10. FIELD AND POOL, OR WILDCAT So. Blanco Pictured Cliffs & Otero Chacra 11. SEC., T., E., M., OR ELK. AND SURVEY OR AREA Sec. 10, T-25-N, R-6-W NMPM	
14. PERMIT NO.	-	15. ELEVATIONS (Show whether D 6692'GI	F, RT, GR, etc.)	Rio Arriba New Mexico	
16.	Check Ap	propriate Box To Indicate I	Nature of Notice, Report, or C		
	NOTICE OF INTENT	TON TO:	SUBSEQ	UENT REPORT OF:	
TEST WATER SHUT-OF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)	M	CLTIPLE COMPLETE BANDON* HANGE PLANS	Completion of Recomb	REPAIRING WELL  ALTERING CASING  ABANDONMENT*  s of multiple completion on Well detion Report and Log form.)	
17. DESCRIBE PROPOSED (proposed work. I nent to this work.)	PR COMPLETED OPER f well is direction	RATIONS (Clearly state all pertine mally drilled, give subsurface loc	ent details, and give pertinent dates extions and measured and true vertic	, including estimated date of starting any cal depths for all markers and zones perti-	
9-18-72	Pictured C 2867' set a WOC 18 ho	it 2877'. Baffle set a	P1 joints 2 7/8", 6.4#, jt 2866'. Cemented with	-55 production casing a 355 cu.ft. cement.	
	at 3808'.	3808'. Ran 123 joir Baffle set at 3797'. nent at 2560'.	nts 2 7/8", 6.4#, J-55 p Cemented with 304 cu.f	roduction casing, 3798' set t. cement. WOC 18 hours.	
PBTD 2866'. Perf'd Pictured Cliffs 2774-86' and 2794-2806' with 24 shots perzone. Frac'd with 30,000# 10/20 sand and 30,100 gallons treated water. Dropped one set of 24 balls. Flushed with 800 gallons.					
	zone. Fra	ac'd with 34,000# 20/	42-60', 3690-96' and 37'/40 sand and 34,400 gallshed with 930 gallons.	46-52' with 24 shots per lons treated water. Dropped	
18. I hereby dytty //	at the foregoing i	true and correct	Petroleum Engineer	December 5, 1972	
(This space for Fe	deral or State off	ice use)		DESSINS	

7 1972 DEC

APPROVED BY CONDITIONS OF APPROVAL, IF ANY: