1000 RIO BRAZOS ROAD AZTEC HM 87410 (805) 334-4178 FAX: (805) 334-4170 Innal, state, nat, unifoed/District M/3distric, Nat

This form is not to be used for reporting packer leakings tests in Southeast New Mexico NORTHWEST NEW MEXICO PACKER LEXKAGE TEST

Page 1 Revised 11/16/98

Operator Consolo Inc Lease Name Jicavilla & Well No 18 (PC)

Location of Well:Unit Letter M Sec 02 Twp 25 Rge 05 API # 30-0 39-2056 700

	NAME OF RESERVOIR OR POOL	TYPE OF PROD. (Oil or Gas)	METHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)	
Upper Completion	. Pichwed Cliff	GAS	Flow	TbG.	
Lower Completion	CharRA	laps	Flow	T6G.	

PRE-FLOW SHUT-IN PRESSURE DATA

Upper	Hour, date shut-in	Length of time shut-in	SI press. Psig	Stabilized? (Yes or No)
Completion	09-24-00	3 Da45		
Lower	Hour, date shut-in	Length of time shut-in	SI press, Psig	Stabilized? (Yes or No)
Completion	09-24-00	3 Days		1

FLOW TEST NO. 1

Commenced at (hour, date)*				Zone producing (Upper or Lower):		
TBME (hour,date)	LAPSED TIME SINCE*	PRESSURE		PROD. ZONE	REMARKS	
		Upper Completion	Lower Completion	TEMP.		
09-25-00	1 Day	245	285		Both Zones Shut-For	
09-26-00	2-Days	258	342		Both Zones Shut-IN	
09-27-00	3-DAYS	300	365		Both Zones Shut-IN	
19-28-00	1- Day	300	78		Lower Zone Playing.	
9-29-0	2 Day	300	81		1. 1- 2	
	·	·				

Production rate during test

Oil;	BOPD based on	Bbls. in	_Hours	_Grav	_GOR
Gas:	MCFPD; Tested thru (C	Orifice or Meter)	•		

MID-TEST SHUT-IN PRESSURE DATA

Upper Completion	Hour, date shut-in	Length of time shut-in	SI press psig	Stabilized? (Yes or No)
Lower Completion	Hour, date shut-in	Length of time shut-in	SI press, psig	Stabilized? (Yes or Nn)

(Continue on reverse side)

FLOW TEST NO. 2

Commenced at (hour, date)**				Zone producing (Upper or Lowr):		
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion	URE Lower Completion	PROD. ZONE	REMARKS	
il: as:			Bbls PD:Tested thru (C		rsGravGOR	
pproved	fy that the inform JAN 11 nservation Division	nation herein cor <u>2001</u> 19_	ntained is true an Operator	d complete to the	bes of my knowledge. NC Shurt	_ New

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note; if, on an initial
- packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at lifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests; all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result s of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).