Form 9-331 (May 1963)

## UNITED STATES SUBMIT IN TRIPLICATE\* (Other instructions on reverse side)

Form approved. Budget Bureau No. 42-R424. 5. LEASE DESIGNATION AND SERIAL NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

9. WELL NO.

76

SUBSEQUENT REPORT OF :

SUNDRY	NOTICES	AND	REPORT	S ON	WFLF2
			_		11 M

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.)

GEOLOGICAL SURVEY

7. UNIT AGREEMENT NAME Lindrith Unit 8. FARM OR LEASE NAME Lindrith Unit

3. ADDRESS OF OPERATOR

El Paso Natural Gas Company

OTHER

PO Box 990, Farmington, NM 87401
LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*
See also space 17 below.)

1490'S, 1710'W

10. FIELD AND POOL, OR WILDCAT So. Blanco Pictured Cliffs Ext.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR ABEA
SEC. 25, T-24-N, R-3-W
NMPM

14. PERMIT NO.

WELL

2. NAME OF OPERATOR

15. ELEVATIONS (Show whether DF, RT, GR, etc.) 7201'GL

12. COUNTY OR PARISH 13. STATE Rio Arriba

NM

REPAIR WELL

(Other)

16.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO: TEST WATER SHUT-OFF FRACTURE TREAT ABANDON\* SHOOT OR ACIDIZE

PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE PLANS

WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING

PREPAIRING WELL ALTERING CASING ABANDONMENT\*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

जिल्हां ग्रह

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*
  - Tested surface casing to 600#/30 min.-OK. 7-15-73
  - TD 3291'. Ran 106 joints 2 7/8", 6.4#, JS production casing, 3281' set at 7-18-73 3291'. Baffle set at 3280'. Cemented with 219 cu.ft. cement. WOC 18 hours. Top of cement at 2105'.
  - PBTD 3280'. Tested casing to 4000#-OK. Perf'd 3178-88', 3200-06' and 3218-30' 8-9-73 with 18 shots per zone. Frac'd with 32,000# 10/20 sand and 32,190 gallons treated water. Dropped two sets of 18 balls each. Flushed with 780 gallons water.



	OIL CON. COM.	The collection for the property of the propert
8. I hereby certify that the foregoing is true and correct	TITLE Drilling Clerk	DATE August 13, 1973
(This space for Federal or State office use)  APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE