

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. Contract No. 122	
2. NAME OF OPERATOR Continental Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla Apache	
3. ADDRESS OF OPERATOR 152 North Durbin St., Casper, Wyo. 82601		7. UNIT AGREEMENT NAME AXI Apache "O"	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1190' FNL, 1168' FWL		8. FARM OR LEASE NAME 2	
14. PERMIT NO.		9. WELL NO. 10. FIELD AND POOL, OR WILDCAT Blanca - Mesaverde	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6863' GR, 6875' KB		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 3, T25N, R4W	
		12. COUNTY OR PARISH Rio Arriba	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Well Progress

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 7 7/8" hole 230-5950' TD. Ran IES and FDC-Gamma Caliper logs. Ran 4 1/2" 10.5# casing landed at 5950' and cemented through fillup collar 5914' with 250 gal. "Mud-Sweep", 210 sacks 50-50 POZ "A", 2% gel, 6 1/2# Gilsonite/sack and 1/2" "D-19". Plug down 3 a.m. 8-2-73. Cemented through stage collar 3564' with 250 gal. "Mud-Sweep", and 120 sacks cement as above. Plug down 6:30 a.m. 8-2-73. Rig released 8-3-73.

Moved in completion rig on 8-29-73 and perforated Mesaverde 5640-50 with 2 JSPF and acidized with 500 gal. 15% HCl with additives. Treated Mesaverde with 16,800 gal. "YF4C", 15,500# 10-20 sand and 2000# 20-40 sand. Perforated Mesaverde 5152-62 with 2 JSPF, acidized with 500 gal. HCl with additives. Treated perfs with 16,000 gal. "YF4C", 2000# 20-40 sand and 15,500# 10-20 sand. Squeezed 5000 gal. 5% HCl acid into perfs. Ran tubing landed at 5640 and opened well to pit to cleanup. Shut well in until flow test can be obtained.

USGS(6) NMOCC(2) EXXON Amoco Aztec File(2)

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Administrative Supervisor

DATE 12/6/73

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: