UNITED STATES

Fig. 3105.53	DEPARTMENT OF THE INTERIOR (Other Instructions of GEOLOGICAL SURVEY			
S (Do not use	SUNDRY NOTICES AND REPORTS ON WELLS this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
OIL GA WELL WELL WELL NAME OF OPERAT	AS XXX OTHER	7. UNIT AGREEMENT NAME		
		8. FARM OR LEASE NAME		
Lynco Oi	l Corporation	Federal USA		
3. ADDRESS OF OPE		9. WELL NO.		
8233 Via	Paseo Del Norte, E-300 Scottsdale, AZ 852	58 1		
See also space 1		10. FIELD AND POOL, OR WILDCAT		
At surface	FNL, 790' FWL	Gavilan P. C.		
185		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA		
		13, T 24N, R 2W		
4. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 7429 GR	Rio Arriba New Mexic		
6.	CL-LA D T L L			


Check Appropriate Box To Indicate Nature of Notice Report of Other Data

		the build				
NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF;			
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF REPAIRING WELL		
FRACTURE TREAT SHOOT OR ACIDIZE		MULTIPLE COMPLETE		FRACTURE TREATMENT ALTERING CASING		
REPAIR WELL		ABANDON* CHANGE PLANS	-	8HOOTING OR ACIDIZING AHANDONMENT XXXX		
(Other)		CHANGE PLANS		(Other)		
ESCRIBE PROPOSED OF CO	11 111 129	SED ADDRESS OF THE SECOND		(ompletion of Kecompletion Report and Log form.)		

SCRIBE PROPOSED OR COMPLETED OFERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set surface plug inside 4-1/2 and 8-5/8 casing annulus from 0-30' with 20 sacks cement. Set dry hole marker. June 29, 1982





11			
3. I hereby certify th	at the foregoing is true and correct	et .	
SIGNED -	A. W. Kizy	TITLE Vice President	June 30, 1982
APPROVED BY	APPROVEI JUL 0.6.1982	D _{TITLE}	DATE
	James F. Sims District engineer	See Instructions on Reverse Side	
		' NMOCC	