

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER		7. UNIT AGREEMENT NAME Canyon Largo Unit
2. NAME OF OPERATOR El Paso Natural Gas Company		8. FARM OR LEASE NAME Canyon Largo Unit
3. ADDRESS OF OPERATOR Box 990, Farmington, New Mexico 87401		9. WELL NO. 201
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1840'S, 1730'E		10. FIELD AND POOL, OR WILDCAT So. Blanco Pictured Cliffs
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 3, T-25-N, R-6-W
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6778'GL		12. COUNTY OR PARISH Rio Arriba
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☒	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)


17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

10-28-73 Tested surface casing; held 600/30 minutes.

10-31-73 T.D. 3025'. Ran 102 joints 2 7/8", 6.4#, J-55 production casing, 3015' set at 3025'. Baffle set at 3015'. Cemented with 234 cu.ft. cement. WOC 18 hours. Top of cement at 1850'.

4-10-74 Tested casing to 4000#-OK.
PBTD 3015'. Perf'd 2904-12', 2928-44' with 16 shots per zone. Frac'd with 32,000# 10/20 sand and 32,760 gallons treated water. Dropped one set of 16 balls. Flushed with 714 gallons water.

APR 16 1974



18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Drilling Clerk DATE 4-15-74

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: