## UNITED STATES

DEPARTMENT OF THE INTERIOR	5. LEASE
GEOLOGICAL SURVEY	SF 078885  6. IF INDIAN, ALLOTTEE OR TRIBE NAME
GEOLOGIONE GORVET	THE TANK THE ON THE TANK
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	Canyon Largo Unit
reservoir. Use Form 3-331-6 for Such proposals.)	8. FARM OR LEASE NAME
1. oil gas X other	Canyon Largo Unit
	9. WELL NO.
2. NAME OF OPERATOR THE PAGE Exploration Company	202  10. FIELD OR WILDCAT NAME
El Paso Exp <del>lorati</del> on Company  3. ADDRESS OF OPERATOR	Lar B <del>ållar</del> d Pictured Cliffs
P.O. Box 289, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.)	Section 5, T-25-N, R-6-W
AT SURFACE: 1760'S, 1020'W AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	Rio Arriba New Mexico  14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.	14. AFT NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	6744' GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	BEREIMER
TEST WATER SHUT-OFF  FRACTURE TREAT	
SHOOT OR ACIDIZE	1 11 1 1004
REPAIR WELL PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
MULTIPLE COMPLETE TO TO	OH COM DIV
CHANGE ZONES DUN 0 2 1	
ABANDON* [] [X] (other)	DIST. 3
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen	rectionally drilled, give subsurface locations and
May 27-28	· · · · · · · · · · · · · · · · · · ·
MOL and RU. Picked up 1 1/4" IJ tubing strin	g and ran 90 joints. Circulated
hole. Spotted 10 sacks cement plug over perf	
through perforations leaving a cement plug fr	
sacks of cement from 2610' to 2080' over Frui	
top. Perforated 2 squeeze holes 50' below su	
spotted a 60 sack plug. Squeezed and left ce	ement plug inside and outside.
casing from 175' to 75'. Spotted 10 sacks ce	
plug and abandon marker.	50 to surface t
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct Production	
SIGNED CA DOWNLAW TITLE Engineer	DATE June 3, 1982
(This space for Federal or State offi	ce use)
APPROVED BY TITLE	DATE Among Chrish
CONDITIONS OF APPROVAL, IF ANY:	
NMOCC Cietary	
.*	$\sqrt{\frac{1}{2}}$
	•