UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

c. 1973	Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	SF 078910
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	1.41.
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
not use this form for proposals to drill or to deepen or plug back to a different ervoir. Use Form 9–331–C for such proposals.)	LINDRITH UNIT COM
	8. FARM OR LEASE NAME
oil gas	LINDRITH UNIT COM
well well other	9. WELL NO.
NAME OF OPERATOR	93
EL PASO NATURAL GAS CO.	10. FIELD OR WILDCAT NAME
ADDRESS OF OPERATOR	SO. BLANCO P.C.
BOX 990, FARMINGTON, NEW MEXICO	11. SEC., T., R., M., OR BLK. AND SURVEY OR
LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA SEC. 29, T-24-N, R-2-W
below.)	NMPM :
AT SURFACE: 1460'S, 1790'E	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	RIO ARRIBA NEW MEXICO
AT TOTAL DEPTH.	14. API NO.
CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
DUTCT FOR ARRESONAL TO: CHRSEOUTAIT REPORT OF	7086' GL
QUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	

(Do not use this form for proposals to drill or to deepen or plug back to a differeservoir. Use Form 9–331–C for such proposals.) \square other well well 2. NAME OF OPERATOR EL PASO NATURAL GAS CO. 3. ADDRESS OF OPERATOR BOX 990, FARMINGTON, NEW MEXICO 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space below.) 1460'S, 1790'E AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTIC REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (NOTE: Report results of multiple completion or zone PULL OR ALTER CASING change on Form 9-330.) MULTIPLE COMPLETE **CHANGE ZONES** ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9/18/78: Spudded well. Drilled surface hole. Ran 3 joints 8 5/8", 24# K-55 surface casing, 122' set at 133'. Cemented with 106 cu. ft. cement. Circulated to surface. 12 hours; held 600#/30 minutes.

Subsurface Safety Valve: Manu. and Type ___ 18. I hereby certify that the foregoing is true and correct TITLE Drilling Clerk 9/19/78 _ DATE _ SIGNED 4 (This space for Federal or State office use)

TITLE DATE CONDITIONS OF APPROVAL, IF ANY:



SEP 2 6 1978