Form 3166-5 (November 1983) (Formerly 9-331) DEPAR	UNITED STATES TMENT OF THE INTER	8UBMIT IN TRIPLICATE*  (Other instructions on re-	Budget Bureau No. 1004-0135 Expires August 31, 1985 5. LEASE DESIGNATION AND BELIAL NO
BUREAU OF LAND MANAGEMENT			Jicarilla Contract 146
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not ture thin form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)			6. IF INDIAN, ALLOTTER OR TRIBE NAME
			Jicarilla Apaghe
OIL CAR OTHER			7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR			8. PARM OR LEASE NAME
Amoco Production Co.			Jicarilla Contract 146
2325 E. 30 St., Farmington, NM 87401 RECEIVED			31
6. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*  See also space 17 below.)  At surface  1660 FNL x 1095 FWL			10. FIELD AND POOL, OR WILDCAT
			Blanco Mesaverde
1990, LMF 3			11. SBC., T., R., M., OR BLK. AND SURVEY OR ARRA
		SUREAU OF FAND MANAGEMENT. FARMINGTON RESOURCE AREA	CHANGE 10 MOEN DET
14. PERBIT NO.	15. ELEVATIONS (Show whether		SW/NW Sec 10, T25N, R5W 12. COUNTY OR PARISH   13. STATE
	6717' GR		Rio Arriba NM
6. Check	Appropriate Box To Indicate	Nature of Notice, Report, or C	
NOTICE OF INT			THAT REPORT OF:
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	
PRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CABING
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL	CHANGE PLANS	(Other)	
(Other)		Completion or Recompl	of multiple completion on Well etion Report and Log form.) including estimated date of starting any
nitrogen foam. Pr 4-23-85. This wor	ressure tested casing rk was done without a	to 1100 psi and retur	icals with 25,000 scf of ned well to production or (016) dated 11-4-86.
		<i>f</i>	
		*	
			The second secon
			:
SIGNED SIGNED	is true and correct  TITLE	Adm. Supervisor	— AGALPTED 14041R860RD
(This space for Federal or State of APPROVED BT	TITLE		DATE NÜV 14 1986
CONDITIONS OF APPROVAL, IF	ANI:		HARMINGTON RESOURCE AREA

\*See Instructions on Reverse Side

RY SM