

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

RECEIVED
DEC - 8 1995

OIL CON. DIV.
DIST. 3

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1660' FSL, 990' FWL, Sec. 34, T-25-N, R-5-W, NMPM

5. Lease Number

Jic Contract 10

6. If Indian, All. or
Tribe Name

Jicarilla Apache

7. Unit Agreement Name

8. Well Name & Number
Jicarilla L #7

9. API Well No.
30-039-22529

10. Field and Pool
So Blanco Pict. Cliffs/
Otero Chacra

11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☒ Abandonment

☐ Change of Plans

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☐ Other -

13. Describe Proposed or Completed Operations

- 11-13-95 MIRU. ND WH. NU BOP. PT BOP. Tbg stuck. TIH w/1 13/16" gauge ring to 3500'. Pkr @ 3522'. Plug #1: pump 23 sx Class "B" cmt down tbg @ 3300-3618'. SDON.
- 11-14-95 TIH w/1 13/16" jet cutter to 3522', did not tag cmt. Pump 23 bbl wtr down tbg, pumping into perfs. TIH w/1 13/16" cutter down tbg to 3498'. Cut tbg & TOOH. TOOH w/106 jts 2 3/8" tbg. TIH w/4 1/2" gauge ring to 3415'. TOOH. TIH w/4 1/2" cmt retainer, set @ 3348'. PT tbg to 1000 psi, OK. SDON.
- 11-15-95 TOOH. TIH, perf 2 circ holes in tbg @ 3342'. TIH to 3325'. Plug #2: pump 8 sx Class "B" cmt @ 3214-3319 inside csg above stuck pkr, tbg stub & plugged cmt retainer'. TOOH. TIH w/4 1/2" cmt retainer, set @ 2704'. Load hole w/16 bbl wtr. PT csg to 500 psi, OK. Establish injection into Pictured Cliffs perfs. Plug #3: pump 43 sx Class "B" cmt below cmt retainer, 47 sx Class "B" cmt above cmt retainer, TOC @ 2085'. TOOH to 772'. SDON.
- 11-16-95 Establish circ down csg & out bradenhead. Plug #4: pump 63 sx Class "B" cmt from 772' to surface. Circ 1 bbl cmt to surface. ND BOP. Cut off WH. Fill 4 1/2" csg w/5 sx Class "B" cmt. Install dry hole marker w/10 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 11-16-95.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 11/20/95

(This space for Federal or State Office use)
APPROVED BY [Signature] Title Chief, Lands and Mineral Resources

CONDITION OF APPROVAL, if any: DEC 7 1995