STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to

	be used for packer lead in Southeast	kage tests	NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST							
Operator			Prod. Co Two. 25	Lease Rge	Jicarilla U	Count	Well 26 No. 26			
wen.	Olin	NAME OF RESERVE		TYPE OF P	ROD.	METHOD OF PROD. (Flow or Art. LIM)	PROD. MEDIUM (Tbg. er Ceg.)			
Upper Completion	P. =			; c 5	; e 3		TX 1			
Lower Completion	wer			= <u>,</u>	. 7	·)	12			
			PRE-I	LOW SHUT-IN P	RESSURE DATA	L				
Upper Completion	Hour, date sh	19/ 2:00 ut-in	Length of time	10 - shut-in	St press. psig		iabilized? (Yes or No) 火产 で iabilized? (Yes or No)			
Lower Completion	Lower		m 3/2	, 27, 7	532		y = x			
				FLOW TEST	NO. 1	·				
nimenced	at thour, date)*			Zone producing (U	pper er Lower):				
•	TIME LAPSED TIME		Upper Completion	PRESSURE			REMARKS			
<u>`</u>	em 5	28 hR	205	520		6011C7 711 Loc. 712028	30 min owly			
	Pm 1/22		205	540	ļ	CHOKE THE	REEZE PARTIALLY			
	nm 1/23		205	544		24MC1 LOC 7ROZE	20 62			
10:00	1/2 CAA	124	205	536		FROZE O	77 24			
0:02	ami/25	24	204	540		FROZE O	, 22 24			
	AM/126		205	531		0N 4 h	R 7202607720			
	on rate di									
\il.		ı BOI	PD based on	Bbls. i	n Hou	rs G	av GOR			
J 2 5:				-TEST SHUT-IN I						
	Hour, date shul-in Length of time shul-i						Stabilized? (Yes or No)			
Upper	Hour, date shut-in Length of time shu				Si press. psig		Stabilized? (Yes or No)			

FLOW TEST NO. 2

Commenced at (hour, de	10) 中中		Zone producing (Upper or Lower):				
TIME	LAPSED TIME	PRESSURE		PROD. ZONE			
(hour, dete)	SINCE **	Upper Completion	Lower Completion	TEMP.	REMAI	IKS	
	İ						
	ļ						
		 					
							
			L				
	ļ						
	<u> </u>						
Production rate d	luring test				*		
Oil:	:BOPD based on			Hours.	Grav	GOR	
725:		MCF	PD: Tested thru	(Ortfice or Meter)):		
lemarks:							
					· · · · · · · · · · · · · · · · · · ·		
	· · · · · · · · · · · · · · · · · · ·						
L							
петеру септу п	FEB 2 5	ld d bu peteru coursiu	ed is true and co	mplete to the best	t of my knowledge.	9	
Approved			19 (perator Δ	Imaca (8)	Vaduet.	
New Mexico O	il Conservation I	Division	/	perator		/	
			В	y Lu	san Wood	2	
مِيْرِ هِي	al Signed by CHAF	NES OHOLDŪ.		~ 2	1221 7		
sy			T	itle	san Wood	en	
Citle DEPUTY	ML & GAS INSPE	C'08 , 767, ∯J)ate			
		·		/200			

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).