

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTRECEIVED
BLMFORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

5. Lease Designation and Serial No.

NOO-C-14-20-8451

6. If Indian, Allottee or Tribe Name

Navajo

7. If Unit or CA, Agreement Designation

8. Well Name and No.

South Blanco Navajo 31#2

9. API Well No.

30 039 22759

10. Field and Pool, or Exploratory Area

Lybrook Gallup

11. County or Parish, State

Rio Arriba County, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other2. Name of Operator BANNON ENERGY INCORPORATED
c/o Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1660' FNL & 940' FWL (SW/4 NW/4)

Unit E, Sec. 31, T24N, R7W

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent☐ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plan to plug as follows:

1. Set cast iron bridge plug at 5350'. Top Gallup perforation 5400' with Gallup top at 5354'.
2. Spot 100' Class B cement plug on top of bridge plug.
3. Spot 100' Class B cement plug across Mesa Verde top (2853') inside pipe.
4. Spot Class B cement plug across Pictured Cliffs (1983') - Fruitland (1626') tops inside pipe.
5. Spot 100' Class B cement plug across Ojo Alamo (1327') top inside pipe.
6. Establish rate down 4 1/2" x 8-5/8" annulus. If able to pump into annulus, pump Class B cement + 4% gel of sufficient volume to fill to 50' below surface casing (243').
7. Spot Class B + 4% gel cement inside 4 1/2" to fill from 50' below surface casing (243') to surface.

All plugs will be spotted with water. Class B cement weighs 15.6 lb./gal. and yields 1.18 cu. ft./sk., Class B + 4% gel weighs 14.1 lb./gal. and yields 1.55 cu. ft./sk.

14. I hereby certify that the foregoing is true and correct

Signed

Title Agent

Date 9/14/94

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

APPROVED
AS AMENDED

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

DISTRICT MANAGER