SHOOT OR ACIDIZE

PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)

REPAIR WELL

(NQTE: Report results of multiple completion or zone

change on Form 9-330.)

UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE Jic. Tribal Cont. #123			
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla- Apache			
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME			
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME Jicarilla 123 C			
1. oil gas well other 2. NAME OF OPERATOR	9. WELL NO. 28E			
El Paso Exploration Company	10. FIELD OR WILDCAT NAME Basin Dakota			
3. ADDRESS OF OPERATOR P.O. Box 289, Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR			
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1550'S, 1520'W	AREA Sec. 6, T-25-N, R-4-W NMPM			
AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	12. COUNTY OR PARISH 13. STATE Rio Arriba New Mexcio 14. API NO.			
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6954' GL			
REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF EPACTURE TREAT SUBSEQUENT REPORT OF: TYPE TREAT				

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
- 5-27-82: Spudded well. Drilled surface hole. Ran 5 joints of 9 5/8", 36#, k-55 surface casing 206' set at 218'. Cemented w/ 224 cu. ft. cmt. Circulated to surface. WOC 12 hours; held 600#/30 minutes.



Subsurface Safety Valve: Manu. and Type		OIL CONT. 3 DIST. 3 Set @				Ft.
18. I hereby certify that the foregoing is to	TITLE	ect Drilling	Clerk	_ DATE	June 4, 1982	
	(This space	for Federal or Sta	te office use	e)		
APPROVED BY	TITLE			DATE _	- Statement	

*See Instructions on Reverse Side

MMOCC