



APPLICATION FOR MULTIPLE COMPLETION

Operator J. Felix Hickman		County Rio Arriba		Date 08-04-83
Address P.O. Box 1258 Farmington, NM 87499		Lease Schmitz		Well No. 2
Location of Well	Unit E	Section 16	Township T25N	Range R3W

All Applicants for multiple completion must complete Items 1 and 2 below.

1. The following facts are submitted:	Upper Zone	Intermediate Zone	Lower Zone
a. Name of Pool and Formation	Blanco Mesa Verde	Ojito Gallup	Dakota
b. Top and Bottom of Pay Section (Perforations)	5865-6137	7134-7424	8008-8050
c. Type of production (Oil or Gas)	Gas	Gas and Oil	Gas and Oil
d. Method of Production (Flowing or Artificial Lift)	Flowing	Flowing	Flowing
e. Daily Production ☒ Actual 3 hr. ☐ Estimated Oil Bbls. Gas MCF Water Bbls.	Bk. Pr. Test 0 3936 Trace	3 hr. Bk. pr. Test	96 546 96 (Frac Water)

2. The following must be attached:

- Diagrammatic Sketch of the Multiple Completion, showing all casing strings, including diameters and setting depths, centralizers and/or turbolizers and location thereof, quantities used and top of cement, perforated intervals, tubing strings, including diameters and setting depth, location and type of packers and side door chokes, and such other information as may be pertinent.
- Plat showing the location of all wells on applicant's lease, all offset wells on offset leases, and the names and addresses of operators of all leases offsetting applicant's lease.
- Electrical log of the well or other acceptable log with tops and bottoms of producing zones and intervals of perforation indicated thereon. (If such log is not available at the time application is filed it shall be submitted as provided by Rule 112-A.)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed J. Felix Hickman Title Agent Date 08-04-83

(This space for State Use)

Approved By [Signature] Title SUPERVISOR Date 08-04-83

NOTE: If the proposed multiple completion will result in an unorthodox well location and/or a non-standard perforation unit in one or more of the producing zones, then separate application for approval of the same should be filed simultaneously with this application.

Township _____ Range _____ County, State of Okla.

36	31	32	33	34	35	36	31
1	6	5	4	3	2	1	6
12	7	8	9	10	11	12	7
13	18	17	16	15	14	13	18
24	19	20	21	22	23	24	19
25	30	29	28	27	26	25	30
36	31	32	33	34	35	36	31
1	6	5	4	3	2	1	6

Handwritten notes:
- Section 8: "Acreage 100"

Handwritten numbers:
- Section 17: "17"

Handwritten numbers:
- Section 16: "16"

Handwritten numbers:
- Section 15: "15"

Handwritten numbers:
- Section 14: "14"

Handwritten numbers:
- Section 13: "13"

Handwritten numbers:
- Section 12: "12"

Handwritten numbers:
- Section 11: "11"

Handwritten numbers:
- Section 10: "10"

Handwritten numbers:
- Section 9: "9"

Handwritten numbers:
- Section 8: "8"

Handwritten numbers:
- Section 7: "7"

Handwritten numbers:
- Section 6: "6"

Handwritten numbers:
- Section 5: "5"

Handwritten numbers:
- Section 4: "4"

Handwritten numbers:
- Section 3: "3"

Handwritten numbers:
- Section 2: "2"

Handwritten numbers:
- Section 1: "1"

Island Township Plat-

-Scale 1-inch to 1-mile- In stock and for Sale by THE OLDS PRESS Tulsa, Oklahoma - Printed in U.S.A.

Township 2 S Range 34 E County, State of Ark

36	31	32	33	34	35	36	31
1	6	5	4	3	2	1	6
12	7	8	9	10	11	12	7
13	18	17	16	15	14	13	18
24	19	20	21	22	23	24	19
25	30	29	28	27	26	25	30
36	31	32	33	34	35	36	31
1	6	5	4	3	2	1	6

Island Township Plat-

-Scale 1-inch to 1-mile- In stock and for Sale by THE OLDS PRESS Tulsa, Oklahoma • Printed in U.S.A.

RECEIVED

AUG - 5 1900

ON COIN

J. Felix Hickman
Schmitz #2
E-16-25-7
Rio Arriba
New Mexico

RECEIVED

AUG - 1962

OIL CON. DIV.
DIST. 3

9 5/8" surface casing @ 212'
177 c. f. cement

7" 23# csg.
Top of Cement @ 2000'

2 1/16" tbg. @ 5993'

MV perfs: 5865'/6137'

2 3/8" 4.7# @ 6250'

Baker Model "D" 4 1/2" packer @ 6250'

7" 23# csg. @ 6300'
531 c.f. cement

GL perfs: 7132'/7424'

4 1/2" liner (11.6#)
6145'/8155'

2 1/16" tbg. set at 8035'

DK perfs: 8008'/8050'

PBTD @ 8117'

Landed @ 8155'
514 cf cement

TD-8155

