

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
Southland Royalty Company

3. ADDRESS OF OPERATOR
P.O. Drawer 570, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 800' FSL & 1650' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Casing Report

SUBSEQUENT REPORT OF:

SEP 15 1982

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

(NOTE) Report results of multiple completion or plug change on Form 9-330.



5. LEASE
NM - 42417

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Capulin Mesa

9. WELL NO.
#2

10. FIELD OR WILDCAT NAME
Gavilan Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Section 31, T25N, R1W

12. COUNTY OR PARISH
Rio Arriba

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
7414' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-9-82 Drilled 7-7/8" hole to 3400'.

9-11-82 Drilled 6-3/4" hole from 3400' to a total depth of 3615'. Ran 117 joints (3583.71') of 2-7/8", 6.5#, J55 casing set at 3595.71'. Cemented first stage with 447 cubic feet of Class "B" containing 50/50 POZ, 6% gel, 1/4# celloflake. Tail in with 59 cubic feet of Class "B" neat containing 1/4# celloflake. Plug down at 2:45 pm, on 9-11-82.

9-12-82 Top of cement at 1300' by temperature survey.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Sherry Shirley TITLE Secretary DATE September 13, 1982

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

NMOCC

SEP 16 1982
BY SMH