

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Taurus Exploration, U.S.A., Inc.

3. Address and Telephone No.
2198 Bloomfield Highway; Farmington, NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1630' FNL, 1050' FWL, Sec. 31, T25N, R1W, NMPM

5. Lease Designation and Serial No.

NM-42417

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.
Capulin Mesa #1

9. API Well No.
30-039-23056

10. Field and Pool, or exploratory Area
Gavilan Pictured Cliffs

11. County or Parish, State
Rio Arriba NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Notified Cuba BLM on 1/23/98.

1/26/98 Pump down 2 7/8" csg. with 25 bbls. water at 2 BPM at 800 lbs, no blow on bradenhead.
Plug #1: 94 sks. class B cement down 2 7/8" csg., displace to 870' WOC.

1/28/98 Load 2 7/8" csg. with 11 bbls. water and attempt to pressure test casing. Pressured to 750 lbs.
Leak down to 250 lbs. in one minute and to 0 lbs in 3 minutes. Tag cement with wireline at 2406'.
Perforate 3 squeeze holes at 283'. Establish circulation out bradenhead with 12 bbls. water.
Plug #2: 90 sks. class B cement from 283' to surface. Circulate good cement out bradenhead. W.O.C.

1/29/98 Cut off wellhead, found cement down 5' in annulus and 2' in casing. Mix 20 sxs. class B cement, fill casing and install P&A marker.

Note: A. Yepa with Rio Puerco BLM witnessed plugging.

14. I hereby certify that the foregoing is true and correct

Signed [Signature] Title Production Foreman Date 2/12/98

(This space for Federal or State office use)

Lands and Mineral Resources

Approved by [Signature] Title _____ Date MAR 10 1998

Conditions of approval, if any:

costs for surface restoration in attached letter (copy - original sent w/NOT)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.