J

ABANDON\*

(other)

orm Approsed. Budget Bureau No. 42-R1424

Surface Casing and Cement

UNITED STATES  DEPARTMENT OF THE INTERIOR  GEOLOGICAL SURVEY	5. LEASE SF 079549  6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME	
	8. FARM OR LEASE NAME	
1 01 726	Phillips 32	
1. oil ka gas well other	9. WELL NO.	
2. NAME OF OPERATOR	2-6	
Joseph B. Gould	10. FIELD OR WILDCAT NAME	
A ADDRESS OF OPERATOR	West Lindrith Gal/Dak	
2829 East 2nd Ave. St 212 Denver Co. 802 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below.) AT SURFACE: 330' FSL & 2310' FEL AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same	Sec. 32, T25N, R3W  12. COUNTY OR PARISH 13. STATE  Rio Arriba New Mexico  14. API NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. FLEVATIONS (SHOW DF, KDB, AND WD)	
REQUEST FOR APPROVAL TO:  TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES  SUBSEQUENT REPORT OF RECE  SUBSEQUENT RE	15. FLEVATIONS (SHOW DF, KDB, AND WD) 1983 (NOTE: Report results of multiple completion or zone SURVienge on Form 9-330.) GTON, N. M.	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 12¼" hole to 313'. Spud well at 8:00 PM . 12-29-82 Ran 7 joints (301 feet) 8-5/8", 24#, J55, ST&C, 8rd casing. Set at 313'. Cemented with 250 sacks, 295 cu. feet, Class "B" containing 1/4#/sack flocele and 3% CaCl<sub>2</sub>. Circulated 35 sks, 41.30 cu. feet, to surface. Plug down at 8:15 AM 12-30-82.

> WOC 12 hours and pressure tested casing and B.O.P. to 600 psig with rig pump. Held OK.

Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct  SIGNED R.D. Simmon'S TITLE Agent DATE	12-30-82
(This space for Federal or State office use)	

APPROVED BY CONDITIONS OF APPROVA ACCEPIEN FOR RECORD

JAN 04 1983

, FARMINGTON DISTRICT Smm

JAN 51983 · See Instructions on Reverse Side

OIL CON. DIV. NMOCC