5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR

Subsurface Safety Valve: Manu. and Type

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

18. I hereby certify that the foregoing is true and correct

DEPARTMENT OF THE INTERIOR	SF-080594-A
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	None
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	Canyon Largo
	8. FARM OR LEASE NAME
1. oil gas	Canyon Largo Unit Com
well well X other	9. WELL NO.
2. NAME OF OPERATOR	318
Bolack Minerals Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Basin Dakota
P.O. Box 255, Farmington, N.M. 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.)	Sec. 13, T24N-R6W, NMPM
AT SURFACE: 1730' fN1, 1850' fW1	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Rio Arriba N.M.
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	30-039-23263
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
DECLIECT FOR APPROVAL TO: CURRENT REPORT OF	6449' Gr. 6462' est. K.B.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	· · · · · · · · · · · · · · · · · · ·
TEST WATER SHUT-OFF \(\sum \) \(D ECEIVE!
SHOOT OR ACIDIZE	
	(NOVE: Report esults of multiple completion or zone -
PULL OR ALTER CASING	change on Form 9-330¢ ⊏ p 8 - 1983
MULTIPLE COMPLETE SEP (12 1983
CHANGE ZONES	OH CON DOLL
	ID MANAGEMENT RESOURCE AREA DIST. 3
(other) Spud FARMINGTON F	ESOURCE AIRES U.S. 3
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*	
Spud well at 6:45 p.m., Sept. 1, 1983. Drilled 12%" hole to 220'. Ran five joints 8 5/8", 24 lb., J-55, 8-rnd casing, set at 214 ft. Cemented with 295 cu. ft. Class B cement with 3% calc. chloride and 1b/sk. cellophane flakes. Good circulation throughout cementing. Circulated 17 cu. ft. to surface. Plug down at 11:45 p.m., 9/1. Waiting on cement.	

(This space for Federal or State office use)

TITLE Agent

__ DATE ___

DATE Sept. 2, 1983

ACCEPTED FOR RECORD

___ Set @ _____ Ft.

SEP 06 1983

*See Instructions on Reverse Side

FARMINGION RESOURCE AREA