Form 3160-5
(November 1983)
(Formerly 9-331)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other Instructions on reverse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM04083

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

1.

OIL WELL [X] GAS WELL [ ] OTHER

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR

Mesa Grande Resources, Inc.

8. FARM OR LEASE NAME

~~Federal~~ *Wildcat*

3. ADDRESS OF OPERATOR

1200 Philtower Building, Tulsa, Oklahoma 74103

9. WELL NO.

#1 ~~Hellcat Federal~~

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1850' FWL and 1700' FNL

10. FIELD AND POOL, OR WILDCAT

Gav. Mancos/W.C. Grnhn-Dk

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 22-T25N-R2W; F

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7215' GR

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	PULL OR ALTER CASING
FRACTURE TREAT	MULTIPLE COMPLETE
SHOOT OR ACIDIZE	ABANDON*
REPAIR WELL	CHANGE PLANS
(Other)	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREATMENT	ALTERING CASING
SHOOTING OR ACIDIZING	ABANDONMENT* [X]
(Other) Spud Report	

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 12¼" hole to 518' and ran 476' of 9 5/8" 36# J-55,
USS surface casing. Cemented with 265 sacks of Class B cement.
(2% Cacl, ¼# D-29 Cello Flake per sack) Had good returns through
cement job, circulated cement to surface. Plug down at 05:45
9/27/84. Waited on cement 12 hours, nippled up blowout preventer
Drilled cement to shoe and tested blowout preventer and casing
to 500# standing pressure for 15 minutes.

18. I hereby certify that the foregoing is true and correct

SIGNED _Gregory R. Phillips_   TITLE _Geochemist_   DATE _9/28/84_

(This space for Federal or State office use)

APPROVED BY _____   TITLE _____   DATE _____

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

NMOCC

See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.