

3 NMOC

1 McHugh

1 File

1 Kenai

1 Marmik

STATE OF NEW MEXICO

ENERGY AND MINERALS DEPARTMENT

## OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease

State ☐Fee ☒

5. State Oil &amp; Gas Lease No.

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Jerome P. McHugh	8. Farm or Lease Name Boyt and Lola
3. Address of Operator P O Box 208, Farmington, NM 87499	9. Well No. 2
4. Location of Well UNIT LETTER <u>D</u> <u>790</u> FEET FROM THE <u>North</u> LINE AND <u>790</u> FEET FROM THE <u>West</u> LINE, SECTION <u>12</u> TOWNSHIP <u>24N</u> RANGE <u>2W</u> NMPM.	10. Field and Pool, or Wildcat Gavilan Mancos/Dakota
15. Elevation (Show whether DF, RT, GR, etc.) 7298' GL; 7310 KB	12. County Rio Arriba

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPERATIONS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	Spud & Surface Casing <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

M.I. & R.U. Four Corners Drilling Company rig #2. Spudded 12 1/4" hole at 11:00 AM on 11-1-84. Drilled to 241'. Ran 6 jts. 9-5/8" O.D., 36#, K-55, 8 Rd. ST&C casing (T.E. 221') set at 232' RKB. Cemented with 125 sks class "B" plus 2% CaCl (total slurry 147.5 cf). P.O.B. at 5:00 PM 11-1-84. Cement circulated. (Pressure tested surface casing and B.O.P. - 600 psi for 30 minutes - held OK.)

RECEIVED  
NOV 05 1984  
OIL CON. DIV.  
DIST. 3

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Jim L. Jacobs Jim L. Jacobs TITLE Geologist DATE 11-2-84

Original Signed by FRANK T. CHAVEZ SUPERVISOR DISTRICT # 3 DATE NOV 05 1984