

5 BLM, Fmn 1 McHugh

1 File

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☒ other

2. NAME OF OPERATOR
Jerome P. McHugh

3. ADDRESS OF OPERATOR
P O Box 208, Farmington, NM 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1650' FSL - 790' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other)

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒ Spud and surface casing.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-7-84 Moved in and rigged up Four Corners Drilling Co. Rig #2. Spudded 12 1/4" hole at 4:00 p.m. 12-6-84. Drilled to 235'. Ran 5 jts. 9-5/8" O.D., 40#, ST&C, limited service csg. T.E. 215.65' set at 227' RKB. Cemented with 125 sx class "B" plus 2% CaCl₂ (147 cf). POB at 10:30 p.m. 12-6-84. (Circulated approximately 2 bbls. cement to surface.).

OIL CON. DIV.
DIST. 3

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs TITLE Geologist DATE 12-7-84

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE DEC 19 1984
CONDITIONS OF APPROVAL, IF ANY:

FARMINGTON RESOURCE AREA

RV smm