UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)

	Budget Bureau No. 42-R1424
Γ	5. LEASE
1	Contract 129
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
ł	Jicarilla Apache
Γ	7. UNIT AGREEMENT NAME
l	NA
Γ	8. FARM OR LEASE NAME
	Apache
Γ	9. WELL NO.
1	144
ľ	10. FIELD OR WILDCAT NAME
1	Lindrith Gallup-Dakota
Γ	11. SEC., T., R., M., OR BLK. AND SURVEY OR
	AREA Sec 13, T24N R4W
Ī	12. COUNTY OR PARISH 13. STATE
	Rio Arriba NM
_[14. API NO.
1	30-039-23663

15. ELEVATIONS (SHOW DF, KDB, AND WD)

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:
TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE

PULL OR ALTER CASING

(other) Amended Sundry

MULTIPLE COMPLETE CHANGE ZONES

REPAIR WELL

ABANDON*

RECE(NOTE REport results of multiple completion or some change on Form 9-330.)

6843' GR

JUN 12 1985

BUREAU OF LAND MANAGEMENT HARMINGTON RESOURCE AREA

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SUBSEQUENT REPORT OF:

The well was spud on March 30, 1985 at 4 pm using Aztec Rig #124. Drilled 12-1/4" surface hole to 401', ran 401' 8-5/8" 24# k55 ST&C casing. The casing landed at 400' and was cemented with 275 sxs, yield 1.26 cu ft, 346.5 cu ft Class B cement, + .075% D65, 0.2% D-74 retarder. Circulate out.

pressure tested easing 1000 #, 30 minutes

*See Instructions on Reverse Side