

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other In-
structions on
reverse side)

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐

b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESER. ☐

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P. O. Box 4289, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with BLM Form 3160-4-1)
At surface 1170'S 1580'E

At top prod. interval reported below

At total depth

OIL CON. DIV.
DIST. 3

RECEIVED

OCT 07 1985

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

5. LEASE DESIGNATION AND SERIAL NO.

SF 078908

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Lindrith Unit

8. FARM OR LEASE NAME

Lindrith Unit

9. WELL NO.

114

10. FIELD AND POOL, OR WILDCAT

S. Blanco Pic. Cliffs

11. SEC. T. R. M., OR BLOCK AND SURVEY OR AREA

Sec. 7, T-24-N, R-2-W
NMMP

12. COUNTY OR PARISH

Rio Arriba

13. STATE

NM

15. DATE SPUDDED 8-26-85 16. DATE T.D. REACHED 8-29-85 17. DATE COMPL. (Ready to prod.) 10-3-85 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 7209' GL 19. ELEV. CASINGHEAD 7209'

20. TOTAL DEPTH, MD & TVD 3475' 21. PLUG, BACK T.D., MD & TVD 3464' 22. IF MULTIPLE COMPL., HOW MANY* One 23. INTERVALS DRILLED BY Rotary 24. PRODUCING INTERVAL(S), OF THIS COMPLETION--TOP, BOTTOM, NAME (MD AND TVD)* 3322-3452' (S. Blanco Pic. Cliffs) 25. WAS DIRECTIONAL SURVEY MADE No 26. TYPE ELECTRIC AND OTHER LOGS RUN Correlation Gamma-Ray Log; Temp Survey; Ind. Electrolog Gamma Ray; Densilog Neutron Gamma Ray; Ind. Electrolog 27. WAS WELL CORED No

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	24.0#	146'	12 1/4"	142 cu ft	
4 1/2"	10.5#	3475'	6 1/4"	206 cu ft	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					1 1/4"	3452'	

31. PERFORATION RECORD (Interval, size and number)

3322, 3324, 3327, 3330, 3338, 3340, 3343, 3346, 3349, 3352, 3364, 3367, 3370, 3380, 3382, 3394, 3397, 3400, 3411, 3414, 3417, 3430, 3433, 3450, 3452 w/1 SPZ.

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
3322-3452	70,000# 20/40 sand&79,242 gals slickwater

33.* PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)					WELL STATUS (Producing or shut-in)	
9-16-85		Flowing - Capable of Comm. HC to be tested when connected					Shut in	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO	
10-3-85	SI 7 Days		→	0	0	0	0	
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)		
SI 736	SI 939	→	No Flow	No Flow	No Flow	0		
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)								

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Shut in to be Sold

TEST WITNESSED BY

Les Hepner

35. LIST OF ATTACHMENTS

Temp Survey

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE

Drilling Clerk

DATE

10-4-85, 1985

*(See Instructions and Spaces for Additional Data on Reverse Side)

FARMINGTON RESOURCE AREA

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

38.

GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	3020'	3195'	ss. white cr-grn s.	Ojo Alamo Kirtland Fruitland Pic.Cliffs	3020'	
Kirtland	3195'	3250'	Gry sh interbedded w/tight gry fine-grn ss.		3195'	
Fruitland	3250'	3314'	Gry carb sh, scattered coals, coals and gry, tight, fine-grn ss.		3250'	
Pictured Cliffs	3314'	3475'	Gry, fine-grn tight, varicolored soft ss.		3314'	