

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Minel, Inc.

3. ADDRESS OF OPERATOR

309 Washington, NE Albuquerque, NM 87108

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1570' FNL and 790' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7335' GR

5. LEASE DESIGNATION AND SERIAL NO.

SF-080566-B

6. IF INDIAN ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Cayias
WELL, N.M.

2

10. FIELD AND POOL, OR WILDCAT

West Lindrith Gallup-Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 2 T25N R3W, NMPM

12. COUNTY OR PARISH 13. STATE

Rio Arriba

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

REEL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANT ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-2-91 Moved in and rigged up Big A Well Service rig #11.
Removed tree and nipples up BOP. Pulled 2-3/8" tubing.

7-3-91 Ran Baker model N-1 bridge plug on tubing and set at 6705'.
Displaced hole with mud weighing 9.0ppg and having a viscosity
of 50 sec/qt. Pressure tested bridge plug to 500psi. - ok.
Spotted a 6 sack, 7 cu. ft., cement plug on top of bridge plug.
Spotted a 12 sack, 14.2 cu. ft., cement plug at 5599'. Spotted
a 45 sack, 53 cu. ft., cement plug at 3910'. Spotted a 12 sack
14.2 cu. ft., cement plug at 2155'. Circulated cement to the
surface through tubing at 264' (33 sacks, 39 cu. ft.)

Will submit final report when marker has been installed
and location rehabid.

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Agent

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

DATE 7-22-91

DATE JUL 23 1991

AREA MANAGER
FARMINGTON RESOURCE AREA

*See Instructions on Reverse Side