

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	
State ☐	Fee ☒
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER-	7. Unit Agreement Name
2. Name of Operator Amoco Production Co.	8. Farm or Lease Name H.L. Butts Gas Com "B"
3. Address of Operator 501 Airport Drive, Farmington, N M 87401	9. Well No. 1
4. Location of Well UNIT LETTER 0 660 FEET FROM THE South LINE AND 2200 FEET FROM THE East LINE, SECTION 25 TOWNSHIP 24N RANGE 1W NMPM.	10. Field and Pool, or Wildcat Wildcat Mesaverde
11. Elevation (Show whether DF, RT, GR, etc.) 7197' GR	12. County Rio Arriba

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Moved in rigged up service unit on 11-13-85. Total depth of the well is 4879' and plugback depth is 4835'. Pressure tested production casing to 3800 psi. Perforated the following intervals: 4432'-4500', 4 jspf, .38" in diameter for a total of 272 holes. No show of oil or gas. Squeezed perfs 4432'-4500' with 50 SX Class B Neat. Perforated intervals: 3992'-4030', 4 jspf, .50" in diameter for a total of 152 holes. No show of gas or oil. Squeezed perf 3992'-4030' with 125 SX Class B Ideal. Spot 100' cement plug at 1870'. Spot cement from 500' to surface. Cement PxA marker and released the rig on 11-26-85.

RECEIVED
DEC 19 1985
OIL CON. DIV.
DIST. 3

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED BSShaw TITLE Adm. Supervisor DATE 12-11-85

Original Signed by CHARLES GHOLSON

DEPUTY OIL & GAS INSPECTOR, DIST. #3

DEC 19 1985

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY: