

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well <input checked="" type="checkbox"/> gas well <input type="checkbox"/> other <input type="checkbox"/>
2. NAME OF OPERATOR Cotton Petroleum Corporation
3. ADDRESS OF OPERATOR 3773 Cherry Crk Dr No. #750, Den, CO 80209
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 2310' FNL 1650' FEL AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE Contract 129	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla Apache	
7. UNIT AGREEMENT NAME NA	
8. FARM OR LEASE NAME Apache	
9. WELL NO. 147	
10. FIELD OR WILDCAT NAME Lindrieth Gallup Dakota W.	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 13 T24N R4W	
12. COUNTY OR PARISH Rio Arriba	13. STATE NM
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 6887' GR	

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Spud & surf csg

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

**RECEIVED**

NOV 25 1985

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

**BUREAU OF LAND MANAGEMENT  
FARMINGTON RESOURCE AREA**

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

A 12-1/4" surface hole was drilled to 400' using Young Drilling Rig 5 on November 14, 1985 at 4:15 pm. Ran 9 jts 8-5/8" 24# J55 ST&C casing, measuring 277.54'. The casing was set at 391' KB and cemented with 280 sacks Class B. 2% CaCl, 1/4# per sack Celo Flake. Circulate 10 bbls to surface. Plug down at 11:40 am November 14, 1985.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ 3 \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Division Prod. Mgr DATE 11/15/85

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

NMOCC