

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

FARMINGTON RESOURCE AREA
FARMINGTON, NEW MEXICO

2. NAME OF OPERATOR

Benson-Montin-Greer Drilling Corp.

3. ADDRESS OF OPERATOR

221 Petroleum Center Building, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1700' FNL 2310' FEL, Section 5, T24N, R1W

14. PERMIT NO.

15. ELEVATIONS (Show whether OP, RT, GR, etc.)

was 7507' GR, sh/be 7551' GR

5. LEASE DESIGNATION AND SERIAL NO.

NM 28695

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Canada Ojitos Unit

8. FARM OR LEASE NAME

Canada Ojitos Unit

9. WELL NO.

37 (G-5)

10. FIELD AND POOL, OR WILDCAT

Puerto Chiquito Mancos

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 5, T24N, R1W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Perforating report

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/19/87

Perforated from 7039' - 7297', 25 settings, two .43" diameter holes each setting

6/22/87

Acidized with 5000 gallons 15% MSR-100, plus 10 gallons A-250 inhibitor and 10 gallons W-5 non-emulsifying agent.

9/11/87

Sandfraced with 5440 barrels YFGO IV (gelled lease crude oil), plus 151,920 pounds 20-40 sand and 153,480 pounds 12-20 sand.

RECEIVED

SEP 16 1987

OIL CON. DIV
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

Virgil L. Stoabs

TITLE Vice President

DATE 9/11/87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side