

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

| | |
|--|---|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | 5. LEASE DESIGNATION AND SERIAL NO. NM-58873 |
| 2. NAME OF OPERATOR JACK A. COLE | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| 3. ADDRESS OF OPERATOR P. O. BOX 191, FARMINGTON, NEW MEXICO 87499 | 7. UNIT AGREEMENT NAME |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1880' FSL, 930' FEL | 8. FARM OR LEASE NAME RINCON |
| 14. PERMIT NO. | 9. WELL NO. 11 |
| 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 7098 GR 7112 KB | 10. FIELD AND POOL, OR WILDCAT ESCRITO GALLUP |
| | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA NE 1/4 SE 1/4 SEC. 31-T24N-R6W |
| | 12. COUNTY OR PARISH RIO ARRIBA |
| | 13. STATE NEW MEXICO |

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETION

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) SPUD & SET SURFACE

X

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-24-'89 SPUD SURFACE HOLE AT 8:15 A.M. TD 270'. RAN 6 JOINTS 8 5/8", 24.0 LB., J-55 CASING. MEASURED 236.43'. SET AT 250.43'. CEMENTED WITH 250 SACKS (295 FT.) CLASS B, 3% CACL AND 1/4 LB. FLOCELE PER SACK. PLUG DOWN 5:30 P.M. 6-24-'89. CIRCULATED 15 BBLs. CEMENT.

6-25-'89 PRESSURE TEST CASING AND B.O.P. TO 600 PSI FOR 1 HOUR. TEST OKAY.

18. I hereby certify that the foregoing is true and correct

SIGNED Dwayne Blanche

TITLE PRODUCTION SUPERINTENDENT

DATE JUNE 26, 1989

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL IF ANY:

TITLE _____

ACCEPTED FOR RECORD

JUN 28 1989

FARMINGTON RESOURCE AREA

BY KH

*See Instructions on Reverse Side

NMOCD