

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.

5. Indicate Type of Lease  
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator  
M.R. Schalk

3. Address of Operator  
P.O. Box 25825, Albuquerque, New Mexico 87125

4. Well Location  
Unit Letter I : 2310 Feet From The South Line and 330 Feet From The East Line  
Section 34 Township 25N Range 3W NMPM Rio Arriba County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
7158' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: Production Casing ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled ahead to 8139' TD. Ran 4½ 11.60#/ft. M-75 casing with DV tools at 3145' and 6495'. Cemented 1st stage with 400 sxs. 50/50 POZ with 2% Gel, 6¼#/sx Gilsonite (yield 1.41 cu. ft. sx. = 564 cu. ft.) Plug down at 2055 hrs. Cement 2nd stage with 365 Cls. B containing 3% Econolite and ¼#/sx Flocele followed by 50 sxs. Cls. B. with ¼#/sx. Flocele. (Yield 3.05 & 1.18 cu. ft. sx = 1172 cu. ft.) Plug down at 0120 hrs. Cemented 3rd stage with 385 sxs. Cls. B containing 3% Econolite and ¼#/sx. Flocele followed by 50 sxs. Cls. B containing ¼#/sx. Flocele (yield 3.05 & 1.18 cu. ft. sx = 1233 cu. ft.) Plug down on 3rd stage at 0540 hrs. Pumped cement to surface.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Steve Schalk TITLE Agent DATE 7-21-89

TYPE OR PRINT NAME Steve Schalk TELEPHONE NO. (505) 881-6649

(This space for State Use)

APPROVED BY Original Signed by FRANK T. CHAVEZ SUPERVISOR DISTRICT DATE JUL 24 1989

CONDITIONS OF APPROVAL, IF ANY: