OIL X WELL X WELL OTHER 2. NAME OF OPERATOR JACK A. COLE JACK A. COLE 3. ADDRESS OF OPERATOR P. O. BOX 191, FARMINGTON, NEW MEXICO 87499-0191 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1870 FNL X 800 FWL 18. ELEVATIONS (Show whether OF, ET, GE, etc.) KB 6595' MSL RIO ARRIBA NEW MEXICO OTHER 8. FARM OR LEASE NAME LARGO SPUR "A" 9. WELL NO. 10. FIELD AND POOL, OR WILDCAT DEVIL'S FORK GALLUP 11. SEC., T., E., M., OR BLE. AND SURVEY OR AREA RIO ARRIBA NEW MEXICO							
November 1983) DEPARTMENT OF THE INTERIOR FOR THE STATEMENT AS THE SUNDRY NOTICES AND REPORTS ON WELL'S OTHER WELL OTHER OF THE STATEMENT OF THE							
DEPARTMENT OF THE INTERIOR STREET AND SURFACE SUNDRY NOTICES AND REPORTS ON WELLE SUNDRY NOTICES AND REPORTS OF SURE STORPHARM SUNDRY SURFACE	om 3160-5 HAUTED CTATES		.c	SUBMIT IN TRIBLICATE	Budget Bureau	Budget Bureau No. 1004-2135 Expires August 31, 1985	
SUNDRY NOTICES AND REPORTS ON WELLE (Do not use this form for management of this to deeped of place to a different reservoir. (Due not use this form for management of this to deeped of place to a different reservoir. (Due not use this form for management of this to deeped of place to a different reservoir. (Due not use this form for management of this place to a different reservoir. (Due not use this form for management of this place to a different reservoir. (Due not use this form for management of this place to a different reservoir. (Due not use this form for management of this place to a different reservoir. (Due not use this form for management of this place to a different reservoir. (Due not use this form for management of this place to a different reservoir. (Due not use this form for management of this place to a different reservoir. (Due not use this form for management of this place to a different reservoir. (Due not use this form for management of this place this	November 1983)	November 1983)		/Other Treemmenters	Expires Augus		
SUNDRY NOTICES AND REPORTS ON WELL (DO NOT USE TO IT OF PROPOSAL OF DETAILS OF THE NAME (DO NOT USE TO IT OF PROPOSAL OF DETAILS OF THE NAME (DO NOT USE TO IT OF PROPOSAL OF DETAILS OF THE NAME (DO NOT USE TO IT O	Formerly 9-331)				1	AND SERIAL NO.	
SUNDRY NOTICES AND REPORTS ON WELLER CONTINUES AND REPORTS ON WELLEST CONTINUES AND REMAINS AND REMAIN		BUREAU OF LAND MANA	AGEMENT	REUZIVED		 	
CDO ROLL USE CHIS FORM for monoposits to drill or to deceeded or blue have to a different reservoir. WILL CASE CONTROL WILL OTHER 2. NAME OF OPERATOR JACK A. COLE 3. ADDRESS OF OFFRATOR P. O. BOX 191, FARMINGTON, NEW MEXICO 87499-0191 10. FIELD AND FROM LEASE NAME LARGO SPUR "A" 10. FIELD AND FROM LEASE NAME LARGO SPUR "A" 10. FIELD AND FROM LEASE NAME LARGO SPUR "A" 10. FIELD AND FROM LEASE NAME LARGO SPUR "A" 10. FIELD AND FROM LEASE NAME LARGO SPUR "A" 10. FIELD AND FROM LEASE NAME LARGO SPUR "A" 10. FIELD AND FROM LEASE NAME SEC. 18-T24N-R6W SEC. 18-T24N-R6W SEC. 18-T24N-R6W SEC. 18-T24N-R6W SEC. 18-T24N-R6W THEN WATER SHOT-OFF INTERTION TO: THE WATER SHOT-OFF INTERTION TO: THEN WATER SHOT-OFF INTERTION TO: THE WATER SHOT-OFF INTERTION TO: THE THEN WATER SHOT-OFF INTERTION TO: THE THE WATER	CLINID	DV NOTICES AND DED	ORTS ON	.WE: IELM	6. IF INDIAN, ALLOTTI	EE OR TRIBE NAME	
O'LL IN SAME OF OPPERENT 2. NAME OF OPPERENT 3. AND CONTROL OF THE STANDARD OF CONTROL OF STANDARD OF STA	SUND	RI NONCES AND RE	on or niue back t	to a different reservoir.			
WELL IN THE COLE 2. NAME OF CREATER 2. NAME OF CREATER 2. NAME OF CREATER 3. PORT OF COLE 4. ADDEER OF OPERATOR 5. PORT OF SEATOR 6. PORT OF SEATOR 7. OLE DAY 191, FARMINGTON, NEW MEXICO 87499-0191 1. DECEMBER 17 relow! 1. DECEMBER 17 relow! 1. DECEMBER 17 relow! 1. See also specify of creating creating creating and in accordance with may disaft requirements.* 8. FARM OR FUL 8. PARK DO FOLL OR WILLOUT 8. PARK DO FOLL OR WILLOUT 1. See also specify of creating creating creating and in accordance with may disaft requirements.* 1. PARK TO FILL X 800 FUL 1. See also specify of creating creating and in accordance with may disaft requirements.* 1. PARK TO FILL X 800 FUL 1. SEE ALSO SPUE 11. SEC ALSO SEE AND SEC ASSUME 1. SEC ASSUME THE CREATING AND	(Do not use this id	Use "APPLICATION FOR PERMIT—"	for such propose	457 12 29 11 19: 45	5		
WELL LA WELL OTHER JACK A. COLE 1. ADDRESS OF OTHERS P. O. BOX 191, FARMINGTON, NEW MEXICO 87499-0191 1. SOLUTION OF WELL DEPOTE IDEATION CIVETY and in accordance with any State requirements." 1870 FNL X 800 FWL 18. PERMIT NO. 18. LENTATIONS (Show whether of NY, CA etc.) 19. PELL AND PROCE OR WILLIAM SEC. 18-T24N-ROW 19. SEC. 18-T24N-ROW REST OF ALEKA LID SEC. 18-T24					7. UNIT AGREEMENT N	AME	
LACK A. COLE JACK A. COLE JACK A. COLE JACK A. COLE JACK A. COLE LACTOR OF VALUE OF PARTINGTON, NEW MEXICO 87499-0191 LOCATION OF VALUE (Report location cirerly and in accordance with any State requirements." See this space 17 refow) 10. First and for foot, or wildcar DEVIL'S FORK GALLUP 11. FERRIT 30. 12. COUNTY OF FALLER IN THE MEXICO RE 6595' MSL 13. COUNTY OF FALLER IN THE MEXICO ROTTER OF INTESTION TO: SOUTH OF OR ALTER CARDO FOLLOR ALTER CARDO FALCTURE TREATMENT ALTERING CARDO FOLLOR ALTER CARDO FRACTURE TREATMENT SECOND OR ACTOR CARDO FRACTURE TREATMENT ALTERING CARDO FRACTURE TREATMENT ALTERING CARDO FOLLOR ALTER CARDO FRACTURE TREATMENT ALTERING CARDO FRACTURE TREATMENT ALTERING CARDO FRACTURE TREATMENT ALTERING CARDO FRACTURE TREATMENT ALTERING CARDO FRACTURE TREATMENT TO ARTER ARTOON FRACTURE TREATMENT ALTERING CARDO FRACTURE TREATMENT ALTERING OF CARDO FRACTURE TREATMENT ALTERING CARDO FRACTURE TREATMENT ALTERING CARDO AND MORE AND MORE FRACTURE TREATMENT ALTERING CARDO AND MORE TREATMENT ALTERING CARDO FRACTURE TREATMENT ALTERING CARDO AND MORE TREATMENT ALTERING CARDO FRACTURE TREATMENT ALTERING CARDO AND MORE TREATMENT ALTERING TO THE ALTER THE ALTER TREATMENT ALTERING TO THE ALTER THE ALTER TO THE ALTER	OIL X GAS	- OTHER	0.5	A HARRY WATON !!	눼		
JACK A. COLE JA				5 1 1 1 1 1 1 1 1 1 	8. FARM OR LEASE NA	ME	
3. ADDRESS OF OFFERIOR P. O. BOX 191, FARMINGTON, NEW MEXICO 87499-0191 10. PIELD AND POOL, OR WILDCAY See High Space 17 Joint 1. See High Space 17 Joint 1. 10. PIELD AND POOL, OR WILDCAY DEVIL'S FORK GALLUP 11. SEC. 12. N. OR BEEK AND SEC. 18-724N-R6W 12. CORPT OR PARISH; 13. SPACE RIO ARRIBA NEW MEXICO Check Appropriate Box To Indicate Nature of Notice. Report, or Other Date NOTICE OF INTENTION TO: NOTICE OF INT		LARGO SPIIR "A	TARCO SPITE "A"				
P. O. BOX 191, FARMINGTON, NEW MEXICO 87499-0191 1. LOCATION OF WILL (Report location clearly and in accordance with any State requirements.* 18. LEVATION OF WILL (Report location clearly and in accordance with any State requirements.* 18. LEVATION OF WILL (Report location clearly and in accordance with any State requirements.* 18. LEVATION OF WILL (Report location clearly and in accordance with any State requirements.* 18. LEVATION OF WILL (Report location clearly and in accordance with any State requirements.* 18. LEVATION OF WILL (Report location clearly and in accordance with any State requirements.* 18. LEVATION OF WILL (Show whether of, NT, CA, CIA.) 18. LEVATION OF WILL (Report location clearly states) 18. LEVATION OF WILL (Show whether of, NT, CA, CIA.) 18. LEVATION OF WILL (Show whether of, NT, CA, CIA.) 18. LEVATION OF WILL (Show whether of, NT, CA, CIA.) 18. Check Appropriate Box To Indicate Nature of Notice. Report, or Other Data NOTICE OF STATES SHOTOFF FRACTURE TREAT SHOT OF ALTER SHOTOFF FRACTURE TREAT SHOT OF ALTON OF WILLIAM OF THE SHORT OF THE COMPLETE COMPLE						· · · · · · · · · · · · · · · · · · ·	
18. Decreased 1 Select 1 Selec	••	TANKENGEN WELL WENT	07/00 01	0.1			
See also space if select. 1870 FNL X 800 FWL 11. SECT. L. W. OR SELE, ADD 12. CORNET OR SELE, ADD 13. FERNIT NO. 14. FERNIT NO. 15. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Date NOTICE OF INTENTION TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDITY ARABODI' 17. DESTRUCT OF DETERMINE OF PLANE SHOOT OR ACIDITY ARABODI' 18. SECT. AL W. OR SELE, ADD NEW MEXICO SECT. ADD A CREATER NEW OR ALIER CASING WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDITY ARABODI' 19. SURFACE CASTING COLORS SURFACE CASTING OCHER SURFACE CASTING OCHER SURFACE CASTING ARABODI' 17. DESTRUCT OF OPERATIONS SET AND CEMENT SURFACE CASING 17. MAY 1991 — SPUD 12.250" SURFACE HOLE AT 15:00 HRS. AND DRILL TO 283'. SET 265.26' OF 8.625" 24# J-55 CASING AT 279'. CEMENT WITH 230 SACKS CLASS "B" CEMENT CONTAINING 3% CALCIUM CHICARDE AND 0.25 LB, SK FLOCELE. CIRCULATED 20 BBL 95 SX) CEMENT. PLUG DOWN AT 10:30 P.M. WOC 8 HRS. TEST CASING TO 600 PSIG FOR 15 MINUTES. NO PRESSURE LOSS OBSERVED.	P. O. BOX 191,						
18. Check Appropriate Box To Indicate Nature of Notice. Report, or Other Date Notice of intention of intenti	4. LOCATION OF WELL (Rep. See also space 17 below						
18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data Test water sent of Indicate Nature of Notice, Report, or Other Data Notice of Intention 70: Substantive Parks of Indicate Nature of Notice, Report, or Other Data Notice of Intention 70: Notice of Indicate Nature of Notice, Report, or Other Data Notice of Intention 70: Notice of Indicate Nature of Notice, Report report of Indicate Nature of							
SEC. 18-T24N-R6W IS. REPARTONS (Show whether or. NT. GR. etc.) (R. Check Appropriate Box To Indicate Nature of Notice. Recort, or Other Data NOTICE OF INTENTION TO: TEST WATER SHOT-OFF PELL OR ALTER CARING ARABODOS* REPART MILLIPPER COMPLETE ARABODOS* REPART WATER SHOT-OFF REPART WATER SHOT-OFF REPART WATER SHOT-OFF REPART WATER SHOT-OFF PELL OR ALTER CARING ARABODOS* (Other) SURFACE CASING TO ARCHER PROCESSED OR ALTER CARING ARABODOS* (Other) SURFACE CASING TO ALTERING CASING ARABODOS* (Other) SURFACE CASING TO ALTERING CASING TO ALTERING CASING TO ALTERING CASING ALTERING CASING ALTERING CASING ALTERING CASING ALTERING CASING TO COMPLETED OPERATIONS (Clearly Mater all pertipent details) and type pertipent details of multitue completion on Wall Completion or results of multitue completion or respective comple					11. SEC., I., R., M., OR SURVEY OR ARE	BLK. AND	
15. PERMIT NO. 15. ELEVATIONS (Show whether or, NT, CR, etc.) 16. Check Appropriate Box To Indicate Nature of Notice. Redort, or Other Date NOTICE OF INTERTION TO: 17. Check Appropriate TRANT SHOOT OR ACIDIEF 18. CLUTTPLE COMPLETE SHOOT OR ACIDIEF S	1870 FNL X 800	FWL					
REPORT OF OPERATIONS SET AND CEMENT CONTAINING 37 CALCIUM CALCASING 17 MAY 1991 - SPUD 12.250" SURFACE HOLE AT 15:00 HRS. AND DRILL TO 283'. SET 265.26' OF 8.625" 24# J-55 CASING AT 279'. CEMENT WITH 230 SACKS CLASS "B" CEMENT CONTAINING 37 CALCIUM CALCIUM 37 CALCIUM CIRCULATED 20 BBL (95 SX) CEMENT. PLUG DOWN AT 10:30 P.M. WOC 8 HRS. TEST CASING TO 600 PSIG FOR 15 MINUTES. NO PRESSURE LOSS OBSERVED.					SEC. 18-T24N-	-R6W	
TEST WATER SHUT-OFF PACTURE TREAT SHOOT OR ACTORING MULTIPLE COMPLETE AAAADON' MULTIPLE COMPLETE AAAAADON' MULTIPLE COMPLETE AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA	14. PERMIT NO.	15. ELEVATIONS (Show	whether DF, RT, (ik, etc.)	12. COUNTY OR PARIS	HI 13. STATE	
TEST WATER SHUT-OFF PACTURE TREAT SHOOT OR ACTORING MULTIPLE COMPLETE AAAADON' MULTIPLE COMPLETE AAAAADON' MULTIPLE COMPLETE AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA		KB 6595'	MST.		RIO ARRIBA	NEW MEXICO	
NOTICE OF INTERTION TO: TEST WATER SHOT-OFF PRACTURE TREAT SHOOT OR ACIDIET SEPAIR WATER SHOT-OFF PRACTURE TREAT SHOOT OR ACIDIET SHORT OF CHANGE PLANS (Other) (Other) (Other) (Note: SURFACE CASING (Note: Report results of multiple completion on Well (Note: Report results of multiple completion on Well (Note: Report results of multiple completion on Well (Note: Surface CASING (Note: Sur							
TEST WATER SHOT-OFF PACTURE TREAT SHOOT OR ACIDIEF SHORT OR ACIDIER (Other) 17. DESCRIBE CONFIRED OF COMPLETED OFFER-WOAR, ICLERITS STATE all pertinent details, and the pertinent date, including estimated date of statums and meanined and true vertical depths for all markers and zones pertinent to this word.) 17. MAY 1991 - SPUD 12.250" SURFACE HOLE AT 15:00 HRS. AND DRILL TO 283'. SET 265.26' OF 8.625" 24# J-55 CASING AT 279'. CEMENT WITH 230 SACKS CLASS "B" CEMENT CONTAINING 3% CALCIUM CHLORIDE AND 0.25 LB./SX FLOCELE. CIRCULATED 20 BBL (95 SX) CEMENT. PLUG DOWN AT 10:30 P.M. WOC 8 HRS. TEST CASING TO 600 PSIG FOR 15 MINUTES. NO PRESSURE LOSS OBSERVED. PACTURE TREATMENT ALTERING WELL ALTERING CASING ANAJONNE ALTERING CASING ALTERING	16.	Check Appropriate Box To 1	ndicate Natur	e of Notice. Report, or	Other Data		
TEST WATER SHOT-OFF PACTURE TREAT SHOOT OR ACIDIEF SHORT OR ACIDIER (Other) 17. DESCRIBE CONFIRED OF COMPLETED OFFER-WOAR, ICLERITS STATE all pertinent details, and the pertinent date, including estimated date of statums and meanined and true vertical depths for all markers and zones pertinent to this word.) 17. MAY 1991 - SPUD 12.250" SURFACE HOLE AT 15:00 HRS. AND DRILL TO 283'. SET 265.26' OF 8.625" 24# J-55 CASING AT 279'. CEMENT WITH 230 SACKS CLASS "B" CEMENT CONTAINING 3% CALCIUM CHLORIDE AND 0.25 LB./SX FLOCELE. CIRCULATED 20 BBL (95 SX) CEMENT. PLUG DOWN AT 10:30 P.M. WOC 8 HRS. TEST CASING TO 600 PSIG FOR 15 MINUTES. NO PRESSURE LOSS OBSERVED. PACTURE TREATMENT ALTERING WELL ALTERING CASING ANAJONNE ALTERING CASING ALTERING		aren on iversette mo	. 1	ACRS	FOURNT REPORT OF:		
FRACTURE TREAT SHOOT OR ACIDIET (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent details and reserved and true vertical depoins for all barrers and sones pertinent to this work.) REPORT OF OPERATIONS SET AND CEMENT SURFACE CASING 17 MAY 1991 - SPUD 12.250" SURFACE HOLE AT 15:00 HRS. AND DRILL TO 283'. SET 265.26' OF 8.625" 24# J-55 CASING AT 279'. CEMENT WITH 230 SACKS CLASS "B" CEMENT CONTAINING 3% CALCIUM CHLORIDE AND 0.25 LB./SX FLOCELE. CIRCULATED 20 BBL (95 SX) CEMENT. PLUC DOWN AT 10:30 P.M. WOC 8 HRS. TEST CASING TO 600 PSIG FOR 15 MINUTES. NO PRESSURE LOSS OBSERVED. DECRETED TO SERVED. JUN1 2 1991 O'L CON. Div.	NO	TICE OF INTENTION 10.					
SHOOT OR ACIDITY REPAIR WELL Other) CHANGE PLANS COUNTY: Report results of multible completion on Well Noter: Report results of multible completion on Well Completion or Recombletion Report and Lor form. REPORT OF OPERATIONS SET AND CEMENT SURFACE CASING 17 MAY 1991 - SPUD 12.250" SURFACE HOLE AT 15:00 HRS. AND DRILL TO 283'. SET 265.26' OF 8.625" 24# J-55 CASING AT 279'. CEMENT WITH 230 SACKS CLASS "B" CEMENT CONTAINING 3% CALCIUM CHLORIDE AND 0.25 LB./SX FLOCELE. CIRCULATED 20 BBL (95 SX) CEMENT. PLUG DOWN AT 10:30 P.M. WOC 8 HRS. TEST CASING TO 600 PSIG FOR 15 MINUTES. NO PRESSURE LOSS OBSERVED. PEGELVE JUN1 2 1991 CON. Divi	TEST WATER SHUT-OFF	PULL OR ALTER CASING		WATER SHUT-OFF	REPAIRING	AELT	
REPAIR WELL (Other) (Other) (Other) (Other) (Note: Report results of multiple completion on Well (Note: Report results of completion on Well (Note: Report results of report results on Well (Note: Report results on Report r	FRACTURE TREAT	MULTIPLE COMPLETE		FRACTURE TREATMENT	ALTERING	CASING	
REPAIR WELL (Other)	SHOOT OR ACIDIZE	ASANDON*				ENT*	
(Other) (Note: Report results of multible completion on Well Connection or Recounsetion for Note and Lor form. 17. Describe Proposed Note. If well is directionally druled, give subsurface locations and give pertinent dates, including estimated date of starting any problem. REPORT OF OPERATIONS SET AND CEMENT SURFACE CASING 17. MAY 1991 - SPUD 12.250" SURFACE HOLE AT 15:00 HRS. AND DRILL TO 283'. SET 265.26' OF 8.625" 24# J-55 CASING AT 279'. CEMENT WITH 230 SACKS CLASS "B" CEMENT CONTAINING 3% CALCIUM CHLORIDE AND 0.25 LB./SX FLOCELE. CIRCULATED 20 BBL (95 SX) CEMENT. PLUG DOWN AT 10:30 P.M. WOC 8 HRS. TEST CASING TO 600 PSIG FOR 15 MINUTES. NO PRESSURE LOSS OBSERVED. DECEMBER 1991 JUN1 2 1991 COND. Division of Completion on Well Completion of Well Completion of Well Completion of Completion		CHANGE PLANS		(Other) SURFACE C	CASING	XX	
17. DESCRIBE PROPOSED OR COMPLETED OPERATION? IClenity state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) REPORT OF OPERATIONS SET AND CEMENT SURFACE CASING 17 MAY 1991 - SPUD 12.250" SURFACE HOLE AT 15:00 HRS. AND DRILL TO 283'. SET 265.26' OF 8.625" 24# J-55 CASING AT 279'. CEMENT WITH 230 SACKS CLASS "B" CEMENT CONTAINING 3% CALCIUM CHLORIDE AND 0.25 LB./SX FLOCELE. CIRCULATED 20 BBL (95 SX) CEMENT. PLUG DOWN AT 10:30 P.M. WOC 8 HRS. TEST CASING TO 600 PSIG FOR 15 MINUTES. NO PRESSURE LOSS OBSERVED. PEGELVE JUN1 2 1991 JUN1 2 1991		(Note: Report results			its of multiple completion	on Well	
REPORT OF OPERATIONS SET AND CEMENT SURFACE CASING 17 MAY 1991 - SPUD 12.250" SURFACE HOLE AT 15:00 HRS. AND DRILL TO 283'. SET 265.26' OF 8.625" 24# J-55 CASING AT 279'. CEMENT WITH 230 SACKS CLASS "B" CEMENT CONTAINING 3% CALCTUM CHLORIDE AND 0.25 LB./SX FLOCELE. CIRCULATED 20 BBL (95 SX) CEMENT. PLUG DOWN AT 10:30 P.M. WOC 8 HRS. TEST CASING TO 600 PSIG FOR 15 MINUTES. NO PRESSURE LOSS OBSERVED. REGELVE JUN1 2 1991		COMPLETED OPERATIONS Clearing state	all perrinent det	ails and give pertinent dat	es including estimated de	to of starting and	
REPORT OF OPERATIONS SET AND CEMENT SURFACE CASING 17 MAY 1991 - SPUD 12.250" SURFACE HOLE AT 15:00 HRS. AND DRILL TO 283'. SET 265.26' OF 8.625" 24# J-55 CASING AT 279'. CEMENT WITH 230 SACKS CLASS "B" CEMENT CONTAINING 3% CALCIUM CHLORIDE AND 0.25 LB./SX FLOCELE. CIRCULATED 20 BBL (95 SX) CEMENT. PLUG DOWN AT 10:30 P.M. WOC 8 HRS. TEST CASING TO 600 PSIG FOR 15 MINUTES. NO PRESSURE LOSS OBSERVED. PEGELVE JUN1 2 1991 OU CON. Divi	proposed work. If	weil is directionally drilled, give subs	uriace locations	and measured and true ver-	tical depths for all marke	rs and zones perti-	
SET AND CEMENT SURFACE CASING 17 MAY 1991 - SPUD 12.250" SURFACE HOLE AT 15:00 HRS. AND DRILL TO 283'. SET 265.26' OF 8.625" 24# J-55 CASING AT 279'. CEMENT WITH 230 SACKS CLASS "B" CEMENT CONTAINING 3% CALCIUM CHLORIDE AND 0.25 LB./SX FLOCELE. CIRCULATED 20 BBL (95 SX) CEMENT. PLUG DOWN AT 10:30 P.M. WOC 8 HRS. TEST CASING TO 600 PSIG FOR 15 MINUTES. NO PRESSURE LOSS OBSERVED. DEGENVE JUN1 2 1991 CON. Divi	nent to this work.)				•		
17 MAY 1991 - SPUD 12.250" SURFACE HOLE AT 15:00 HRS. AND DRILL TO 283'. SET 265.26' OF 8.625" 24# J-55 CASING AT 279'. CEMENT WITH 230 SACKS CLASS "B" CEMENT CONTAINING 3% CALCIUM CHLORIDE AND 0.25 LB./SX FLOCELE. CIRCULATED 20 BBL (95 SX) CEMENT. PLUG DOWN AT 10:30 P.M. WOC 8 HRS. TEST CASING TO 600 PSIG FOR 15 MINUTES. NO PRESSURE LOSS OBSERVED. DEGET 1991 JUN1 2 1991 CV. CON. Div.		REJ	PORT OF OP	ERATIONS			
17 MAY 1991 - SPUD 12.250" SURFACE HOLE AT 15:00 HRS. AND DRILL TO 283'. SET 265.26' OF 8.625" 24# J-55 CASING AT 279'. CEMENT WITH 230 SACKS CLASS "B" CEMENT CONTAINING 3% CALCIUM CHLORIDE AND 0.25 LB./SX FLOCELE. CIRCULATED 20 BBL (95 SX) CEMENT. PLUG DOWN AT 10:30 P.M. WOC 8 HRS. TEST CASING TO 600 PSIG FOR 15 MINUTES. NO PRESSURE LOSS OBSERVED. DEGET 1991 JUN1 2 1991 CV. CON. Div.		SET AND	CEMENT SU	RFACE CASING			
OF 8.625" 24# J-55 CASING AT 279'. CEMENT WITH 230 SACKS CLASS "B" CEMENT CONTAINING 3% CALCIUM CHLORIDE AND 0.25 LB./SX FLOCELE. CIRCULATED 20 BBL (95 SX) CEMENT. PLUG DOWN AT 10:30 P.M. WOC 8 HRS. TEST CASING TO 600 PSIG FOR 15 MINUTES. NO PRESSURE LOSS OBSERVED. DEGETIVE JUN1 2 1991		-					
OF 8.625" 24# J-55 CASING AT 279'. CEMENT WITH 230 SACKS CLASS "B" CEMENT CONTAINING 3% CALCIUM CHLORIDE AND 0.25 LB./SX FLOCELE. CIRCULATED 20 BBL (95 SX) CEMENT. PLUG DOWN AT 10:30 P.M. WOC 8 HRS. TEST CASING TO 600 PSIG FOR 15 MINUTES. NO PRESSURE LOSS OBSERVED. DEGETIVE JUN1 2 1991	17 3/43/ 1001	CDUD 12 250" SUPEACE I	HOIF AT 15	OO HRS. AND DRIT	L TO 283'. SET	265.26	
CEMENT CONTAINING 3% CALCIUM CHLORIDE AND 0.25 LB./SX FLOCELE. CIRCULATED 20 BBL (95 SX) CEMENT. PLUG DOWN AT 10:30 P.M. WOC 8 HRS. TEST CASING TO 600 PSIG FOR 15 MINUTES. NO PRESSURE LOSS OBSERVED. DEGETYE JUN1 2 1991	1/ MAI 1991 -	OF 0 6351 344 I 55 CA	STNC AT 27	O' CEMENT WITH	230 SACKS CLASS	3 "B"	
CIRCULATED 20 BBL (95 SX) CEMENT. PLUG DOWN AT 10:30 P.M. WOC 8 HRS. TEST CASING TO 600 PSIG FOR 15 MINUTES. NO PRESSURE LOSS OBSERVED. DEGELVE JUN1 2 1991		OF 8.525 Z4# J=33 CAS	CALCTIM CU	TOPTHE AND 0 25 I	B /SX FLOCELE.		
TEST CASING TO 600 PSIG FOR 15 MINUTES. NO PRESSURE LOSS OBSERVED. REGEIVE JUN1 2 1991 CON. Divi		CEMENT CONTAINING 3% (CALCIUM CH	TOKIDE AND U.23 I	10.30 P M MOC	9 HRS	
DEGEIVED JUNI 2 1991 OU CON. DIV		CIRCULATED 20 BBL (95	SX) CEMEN	I. PLUG DOWN AI	TU.JU I.M. WOO	TIND.	
Ou CON. Div		TEST CASING TO 600 PS	IG FOR 15	MINUTES. NO PRES	SORE TOSS OBSER	(VED.	
Ou CON. Div							
Ou CON. Div							
Ou CON. Div					A		
Ou CON. Div				in i			
Ou CON. Div		·		K			
Ou CON. Div				11 /7			
O'U, CON. DIM.					IUN1 2 1991		
					CON DIV		
				•			
18. I hereby certify that the foregoing is true and correct							
18. I hereby certify that the foregoing is true and correct							
18. I hereby certify that the foregoing is true and correct							
18. I hereby certify that the foregoing is true and correct							
18. I hereby certify that the foregoing is true and correct			 				
	18. I hereby certify that t	he foregoing is true and correct					

(This space for Federal or State office use)