

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

KLM Oil & Gas Inc.

3. Address and Telephone No.

Box 151, McLouth, KS 66054

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Surface Location: 1650'FSL & 1710'FWL, S33 T24N, R1W
NMPM

5. Lease Designation and Serial No.
SF079352-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Browning Federal 33-1

9. API Well No.

30-039-25108

10. Field and Pool, or Exploratory Area

W. Puerto Chiquito Mar

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plug well as follows: Knock existing bridge plug set at 5900' into open hole below 7" casing shoe at 5980'. Set retainer 5895'. Dispose of water out of reserve pit. Plug #1: spot 20sx cmt (allocmt 1.18 yield & 15.6 ppg) on top of retainer at 5895'. Plug #2: set retainer at 5272', pump 20sx cmt to cover perforated interval under retainer. Plug #3: spot 30sx plug from 4863' to 4763'. Plug #4: spot 30sx plug from 4059' to 3959'. Plug #5: Spot 55sx cmt from 2987' to 2761'. Plug #6: Spot 20sx cmt from 1793' to 1693'. Plug #7: Spot 80sx plug from 422' to surface. Cut off head. Weld on dry hole marker. P&A work completed 4/16/92. Have not yet completed reclaiming pit & pad. Hole is filled with 9.1 ppg mud between plugs. Plugs were spotted through tubing by the pump and displacement method.

14. I hereby certify that the foregoing is true and correct

Signed

John C. Magill

Title

Agent for KLM Oil & Gas Inc. Date 4/17/92

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

APPROVED

AREA MANAGER