

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-039-25168
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No. NA
7. Lease Name or Unit Agreement Name MILLER COM
8. Well No. 1
9. Pool name or Wildcat LINDRITH DAKOTA EXT.
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 7163

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
MOBIL PRODUCING TEXAS & NEW MEXICO, INC.

3. Address of Operator
P O BOX 633 MIDLAND, TX 79702

4. Well Location
Unit Letter G : 1835 Feet From The NORTH Line and 1990 Feet From The EAST Line

Section 17

Township 24N

Range 2W

NMPM RIO ARRIBA

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

7163

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

DRILLED 11 HOLE TO 3300' AND 8 3/4 INCH HOLE TO 7903'. RIH W/7 INCH L80 23# LTC CSG. DV TOOL @ 2343'. 27 CENTRILIZERS SET. LEAD W/580 SXS 65:35:6 CL 'G' +6% D20 + .5% D112 + 1/4 PPS CELLPFLAKE (12.4, 1.18 9.72). TAIL W/300 SXS CL 'G' +2 PPS SILICAFUME + .8 GPS LATEX + .2 GPS M45 + .15 GPS D604. (15.8, 1.17, 4.14). CIRC. THROUGH DV TOOL. DID NOT CIRC. ON 1ST STAGE. SECOND STAGE LEAD W/900 SXS CL 'G' + 6% D20 + .5 D112 + 1/4 PPS CELLO-FLAKE (12.4, 1.84, 9.78). TAIL W/100 SXS CL 'G' + 2% CACL + 1/4 PPS CELLO-FLAKE (5.8, 1.17, 5.01) CIRC 101 SXS TO PIT.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley Todd

TITLE ENV. & REG. TECHNICIAN

DATE 5-26-92

TYPE OR PRINT NAME SHIRLEY TODD

TELEPHONE NO. 915-688-2585

(This space for State Use)

Original Signed by CHARLES SWOLSON

APPROVED BY

DEPUTY OIL & GAS INSPECTOR, DIST. #

DATE MAY 28 1992

CONDITIONS OF APPROVAL, IF ANY: