

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen on reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: September 30, 1990

5. Lease Designation and Serial No.

JTC 149

6. If Indian, Allottee or Tribe Name

JICARILLA APACHE

7. If Unit or CA, Agreement Designation

JICARILLA APACHE F

8. Well Name and No.

16

9. API Well No.

30-039-25256

10. Field and Pool, or Exploratory Area

DAKOTA SAND

11. County or Parish, State

RIO ARRIBA, NEW MEXICO

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

AMERADA HESS CORPORATION: ATTN: MIKE JUMPER

3. Address and Telephone No.

P.O. BOX 2040, HOUSTON, TEXAS 77252

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

970' FNL & 800' FEL SEC. 17 T25N-R5W

RECEIVED
NOV 23 1994

OIL CON. DIV.
DIST. 3

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection

DRILLING COMPLETION

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

M.I. & R.U. ARAPAHOE DRILLING RIG #11 AND SPUDDED 12-1/4" HOLE @ 8 P.M. 10-06-94. DRILLED 0' TO 370'. R.U., RAN & CMTD. 8 JTS. 8-5/8" OD 24# K-55 CSG. @ 365' & CMTD. W/260 SK. CL. "B" CEMENT. PLUG DOWN @ 7:30 A.M. 10-07-94. WOC. INSTALLED A 11" 3000# C-22 CASINGHEAD. TIH W/BIT & TAGGED CEMENT @ 325'. DRILLED CMT. & PLUG. BEGAN DRILLING 7-7/8" HOLE UNDER 8-5/8" SURF. CSG. & DRILLED TO 7,300' T.D. RU & LOGGED W/SCHLUMBERGER FROM 7,300'-365' W/GR TO SURFACE. L.D., D.P. & DC'S. DRILL TO 7,345', R.U. RAN & CMTD. 172 JTS. 5-1/2" O.D. 15.5 # CSG. SET @ 7,344' & DOWELL CEMENTED W/600 SK 35/65 POZG & TAIL W/200 SK CLASS "G". 1ST STAGE W/PLUG DOWN @ 12:45 P.M. ON 10-20-94. PRESS TO 2000 PSI. FLOAT O.K. CIRC. 5 HRS. 2ND STAGE W/PLUG DOWN @ 5:15 P.M. 10-20-94. CEMENT W/552 SK 35/65 POZG & TAIL W/100 SK "G" DROP PLUG. D.V. TOOL WOULD NOT CLOSE SHUT IN CSG. W/350 PSI. HOLD 4 HRS. RELEASE PRESSURE. NO FLOW BACK. TOTAL DISPLACEMENT 92 BBL H2O.

CIRCULATED 15 BBLs OF CMT TO SURFACE ON 8-5/8" CSG. CMT. JOB.
1ST STAGE CIRC. 23 BBL CMT. TO PIT ON 5-1/2" CSG. CMT. JOB.
2ND STAGE CIRC. 50 BBL TO SURFACE ON 5-1/2" CSG. CMT. JOB.
RELEASE RIG @ MIDNITE 10-20-94

14. I hereby certify that the foregoing is true and correct

Signed Mike Jumper

Title ADM. SUPVSR. DRLG. SVS.

Date 11-04-94

(This space for Federal or State office use)

Approved by [Signature]
Conditions of approval, if any.

Title Chief, Lands and Mineral Resources

Date NOV 22 1994