STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## **OIL CONSERVATION DIVISION**

Page 1 Revised 10/01/78

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator	MERI	DIAN	OIL INC				_ Lease	CANYON LARGO UNIT			Well No.	287M		
Location of Well:	Unit	E	Sect.	3	Twp.	025N	Rge.	00 <i>6</i> W	Count	v RIC	ARRIBA	<u>.</u>		
		!	NAME OF	RESE	RVOIR OR POOL		<del></del>	E OF PROD	- $-$	ETHOD O			MEDIUM	
							(Oil or Gas)			(Flow or Art. Lift)			; or ('sg')	
Upper	ME	MESAVERDE					GAS FLOW			OW	-	TUBIN	īG	
Conspletion	+						<del> </del>							
Completion	DA	DAKOTA					GAS		FI	FLOW		TUBING		
					PRE-FLO	W SHUT-	N PRESS	URE DAT	'A					
Upper	Hou	Hour, date shut-in Length of time shut-in			SI press. psig			Stabilized? (Yes or No)						
Completion	7	- '/		<u>v</u>	2/6	<i>h</i> /5	7	8 4						
Lower	9	- 7	9	<u>_</u>	168	1	17,	10				-		
Completion					168	<i>h</i> , s	/ -							
C		1.34	a.14=	ar		FLOW T	EST NO.				<del>//</del>	1		1
	at (hour	t (hour,date)* 9-14-9(								Upper or Le	ower)	VER		
TIME			ED TIME		PRESSURE			_	ZONE					
(hour,date)			NCE*		Upper Completio	Completion	ompletion TEMP			REMARKS				
3-14-9	2	6	861	٤.	351	2	40			lowe	rZone	= 0 /	pen fo	~ <i>F.</i>
-15-90	6	198	241	5	729	9	03							
9-16.	9	<u>ا</u> ھ	6 40		782	18	) 5							
·	-				132	/ 0	2							
						ļ				Г	) [5] (	图	ME	
	╁									- In		/ Lizza i	<u> </u>	<u>.</u>
										Ø	a oct	3 0	1996	~/
										<u>(1)</u>			l. DM	r7
Production	rate du	ring test	<u> </u>		<u> </u>								<del>10 0 0 0</del>	Vu
											[3	NgT.	. <b>3</b>	
Oil:		_ вор	D based or	n	Bbls	s. <u>in</u>	Hou	ırs		Grav		GOR _		
Gas:				мс	FPD; Tested the	nı (Orifica	or Matar):							
	-					.a (Ormee	or Michely.							
	-,				MID-TES	T SHUT-I	N PRESSI	JRE DAT.	A					
Upper	How	Hour, date shut-in Length of time shut-in								abilized? (Yes	or No)			
Completion														
Lower	Нош	r, date shu	t-in		Length of time sl	hut-in	SI press. psig				abilized? (Yes	or No)		

(Continue on reverse side)

معمد بمسر

	<del></del>		FLOW TEST	ΓNO. 2						
Commenced	at (hour.date)**			Zone producing (Upper or Lower):						
TIME	LAPSED TIME	PR	ESSURE	PROD. ZONE						
(hour.date)	SINCE**	Upper Completion	Lower Completion	ТЕМР.	REMARKS					
			1	1						
!										
			1							
[										
	<u> </u>									
			3							
Production	rate during test									
				•						
Oil:	BOPD bas	ed on	Bbls. in	Hours.	Grav. GOR					
Gas:		MCFPD; Te	sted thru (Orifice or I							
Remarks:										
I hereby cer	rtify that the informa	tion herein contained	is true and complete	to the best of my kr	nowledge.					
	10 10A	*		0						
Approved	UCT II		19 96	_Operator ////	enctor Desauseus, Inc					
	0	_		1	1 0-					
New Mex	ico Oil Conservation	n Division		By All	or stay					
Ву	1 most	/ l'interna		Title QOU	tion associate					
•	- Children	- And Alle	· · · · · · · · · · · · · · · · · · ·	_ ine gove	AIN COLORGIAN					
Title	Vegal	volt TV	Spectar	Date						
	100	1		<del></del>						

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after except that the previously produced zone shall remain shut-in while the zone which actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be connected on all multiple completions within seven days
  7. Pressures for gas-zone tests must be measured on each zone with a deadweight following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization, both zones shall remain shur-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days if the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1

- was previously shut-in is produced.
- pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be mously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gaz zone.
- 8. The results of the above described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division of Northwest New Mexico Packer Leakage Test form Revised 10/01/78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).