

(SUBMIT IN TRIPLICATE)

Jicarilla

Indian Agency

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee **Contract #10**

Lease No.

X		

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	X	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	X
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 1, 1960

Jicarilla

Well No. **1-4** is located **985** ft. from **N** line and **805** ft. from **W** line of sec. **4**

SW/4 Sec. 4
(¼ Sec. and Sec. No.)

24N 5W
(Twp.) (Range)

RMP
(Meridian)

Otero

Rio Arriba

New Mexico

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is **6743** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Set 10 3/4" casing at 212', 2-27-60, with spider. Cemented to surface with 175 sz. Moved in rotary, drilled out 3-31-60. Drilling at 1363' 4-1-60. Original plans changed after O.C.C. Case #1911, Order #A-1629. Now will set three strings 2 7/8" new upset tubing. Upper string at approx 3700' or through Chacra with cement to 600' above Pictured Cliffs. Second string through Gallup at approx 6100' with cement 600' above Gallup. Third string through Dakota at approx 7200' with cement 600' above Dakota. All strings to be centralized through pay zones. Each zone to be stimulated with frac. Gallup with oil-sand, P.C. or Chacra and Dakota water-sand.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **JOHNSTON-SHERR**

Address **3010 Monte Vista Blvd., N. E.**

Albuquerque, New Mexico

By **W. R. Johnston**

Title **Operator**

(SUBMIT IN TRIPLICATE)

Indian Agency **Jicarilla**

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee **Contract #10**

Lease No. _____

X		

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	X	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	X
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 1, 1960

Jicarilla
Well No. **1-4** is located **985** ft. from **N** line and **805** ft. from **W** line of sec. **4**
NW/4 Sec. 4 (1/4 Sec. and Sec. No.) **24N** (Twp.) **5W** (Range) **NMP** (Meridian)
Otero (Field) **Rio Arriba** (County or Subdivision) **New Mexico** (State or Territory)

The elevation of the derrick floor above sea level is **6743** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Set 10 3/4" casing at 212', 2-27-60, with spudder. Cemented to surface with 175 sz. Moved in rotary, drilled out 3-31-60. Drilling at 1363' 4-1-60. Original plans changed as per O.C.C. Case #1911, Order #R-1629. Now will set three strings 2 7/8" new upset tubing. Upper string at approx 3700' or through Chacra with cement to 600' above Pictured Cliffs. Second string through Gallup at approx 6100' with cement 600' above Gallup. Third string through Dakota at approx 7200' with cement 600' above Dakota. All strings to be centralized through pay zones. Each zone to be stimulated with frac. Gallup with oil-sand, P.C. or Chacra and Dakota water-sand.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **JOHNSTON-SHEER**

Address **3010 Monte Vista Blvd., N. E.**

Albuquerque, New Mexico

By **W. R. Johnston**

Title **Operator**