

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

McElvain Oil & Gas Properties, Inc.

3. Address and Telephone No.

1050 17th St. Suite 710 Denver, CO 80265 303-893-0933

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1080' FNL & 1500' FWL Section 3, T25N, R2W, NMPM

5. Lease Designation and Serial No.

NM98693

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Elk Com #1

9. API Well No.

30-039-25874

10. Field and Pool, or Exploratory Area

Blanco Mesaverde

11. County or Parish, State

Rio Arriba, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- | | |
|--|--|
| <input type="checkbox"/> Abandonment | <input type="checkbox"/> Change of Plans |
| <input type="checkbox"/> Recompletion | <input checked="" type="checkbox"/> New Construction |
| <input type="checkbox"/> Plugging Back | <input type="checkbox"/> Non-Routine Fracturing |
| <input type="checkbox"/> Casing Repair | <input type="checkbox"/> Water Shut-Off |
| <input type="checkbox"/> Altering Casing | <input type="checkbox"/> Conversion to Injection |
| <input type="checkbox"/> Other | <input type="checkbox"/> Dispose Water |

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud @4:30 PM 07/03/98, Drill 12 1/4" surface hole to 344'. Run 8 joints (320.11') of 9 5/8", 36ppf, J-55, ST&C, Paragon ERW casing with Howco cement nose guideshoe on bottom and one 9 5/8 x 12 1/4 bowspring centralizer @ 320'. CSA 334'. Cement with 190 sacks (224.2 cf) Class B with 2% CaCl & 0.25 pps celloflake. Good circulation throughout job. Circulated 10 bbls (48 sacks) good cement to surface. Plug down @ 2:00 AM, 07/04/98. WOC 12 hours. Test surface casing and BOPE to 600 psig.

14. I hereby certify the foregoing is true and correct

Signed

Title Agent

Date 11/04/98

(This space for Federal or State office use)

Lands and Mineral Resources

DEC 4 1998

Approved by

Title

Date

Conditions of approval, if any.