

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT--" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

McElvain Oil & Gas Properties, Inc.

3. Address and Telephone No.

1050 17th Street Suite 710 Denver, CO 80265 303-893-0933

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1080' FNL & 1500' FWL Section 3, T25N, R2W, NMPM

5. Lease Designation and Serial No.

NM98693

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Elk Com #1

9. API Well No.

30-039-25874

10. Field and Pool, or Exploratory Area

Blanco Mesaverde

11. County or Parish, State

Rio Arriba, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☒ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Drill 6 1/4" hole to 6396'. Run induction Gamma Ray Spectral Density/Epithermal Neutron log from 6388' - 4150'. Run 53 joints (2346.56') 4 1/2" 10.5#, J-55, ST&C ERW casing with TIW LA float shoe on bottom and L landing collar one joint up. Set liner hanger at 4039'. FC @ 6349'. Shoe @ 6395'. Cement liner with lead slurry of 176 sacks 35/65/6 Class G Poz (313.28 cf) with 0.25 pps celloflake, 0.4% FLA, 0.15 Dispersant. Tail in with 101 sacks (118.17 cf) Class G with 0.25 pps celloflake and 0.4% FLA. Reversed out, no cement. Plug down at 8:30 PM 07/21/98. Job complete at 9:15 PM 07/21/98.

14. I hereby certify the foregoing is true and correct

Signed R. E. Fiddle

Title Agent

Date 11/04/98

(This space for Federal or State office use)

Lands and Mineral Resources

DEC 4 1998

Approved by [Signature]

Title

Date

Conditions of approval, if any:

Identify and report top of cement.