

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

5. Lease Designation and Serial No.
NM01397

SUNDRY NOTICES AND REPORTS ON WELLS 00 JUN -9 PM 1:28
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
McElvain Oil & Gas Properties Inc.

3. Address and Telephone No.
1050 17th Street, Suite 1800, Denver, CO 80265 (303) 893-0933

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1310 ' FSL - 1910 ' FWL, Section 3, T25N, R2W, NMPM

7. If Unit or CA, Agreement Designation

8. Well Name and No.
Elk Com No. 1A

9. API Well No.
30 - 039 - 26403

10. Field and Pool, or Exploratory Area
Blanco Mesa Verde

11. County or Parish, State
Rio Arriba, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☒ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)
Spud 12.250" surface hole at 2:45 AM, 05/21/00. Drill to TD of 335 '. Run 311.29 ' of 9.625", 36 ppf, K-55, ST&C casing with cement nose guide shoe on bottom and 12.250" X 9.625" bowspring centralizers at 324 ', 191 ', and 58 '. Cement with 20 bbl fresh water preflush followed by 175 sacks (206.50 cf) Class B with 3 % CaCl and 0.25 pps celloflake. Mixed and pumped slurry at 15.6 ppg at 4 BPM. Displace with 22.5 bbls fresh water. Plug down to 291 ' at 3:45 PM, 05/21/00. WOC 15 hours. Nipple up BOPE. Test blind rams, pipe rams, and choke manifold to 600 psig for 30 minutes, OK.

14. I hereby certify the foregoing is true and correct

Signed Patricia M. Hester

Title Agent

Date 6/05/00

(This space for Federal or State office use)

Approved by Patricia M. Hester
Conditions of approval, if any:

Title Lands and Mineral Resources

Date 7-12-00