			1
Submit 3 Copies to Appropriate District Office	State of New Mexico Energy, Minerals and Natural Resources D	Pepartment	Form C-103
DISTRICT I P.O. Box 1980, Hot 3s, NM 89240	OIL CONSERVATION DIA P.O. Box 2082	WELL API NO.	0/- 039 - 26789
<u>DISTRICT II</u> P.O. Drawer DD Artesia, NM 88210	Santa Fe, New Mexic 589504-	5. Indicate Type	1
<u>DISTRICT III</u> 1000 Rio Brazos Rd., Aztec, NM 8741	i ne	CEIVED 6. State Oil & G	
CLINDRY	NOTICES AND REPORTS OF WELLS	DIV	
(DO NOT USE THIS FORM FOR DIFFERENT RE (FOR	PROPOSALS TO DRILL OR TO DEEP PROPOR PLU SERVOIR. USE "APPLICATION FOR PSE (INT)" M C-101) FOR SUCH PROPOSALS.)		or Unit Agreement Name
1. Type of Well: OIL GAS WELL WELL			
2. Name of Operator		8. Well No.	
McElvain Oil & Gas Pr	coperties, Inc.		2
3. Address of Operator		9. Pool name or	
	te 1800, Denver, CO 80265	В	lanco Mesa Verde
4. Well Location Unit Letter P: 660 Feet From The South Line and 660 Feet From The East Line			
Section 9	Township 25N Range	2W NMPM	Rio Arriba County
	10. Elevation (Show whether DF,RK) 7293 GL		
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK	DIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING		
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT			
PULL OR ALTER CASING CASING TEST AND CE		SING TEST AND CEMENT JOB $oxed{oxtimes}$	
OTHER: OTHER:		HER:	
SEE RULE 1103. September 5, 2001: Dri. (2527.17') of 4 1/2" 1 1/2" X 6 1/4" bowspring drill pipe. Set end of Centralizers at 5864', (180.9 cf) of 65/35 Cla to yield 2.01 cf/sk. Ta 0.25 pps celloflake, 0 circulation until 40 bb	Operations. (Clearly state all pertinent details, and give all 6 1/4" hole to 6175' with air. 0.5 ppf J-55 casing with float show the control of the control	Run deviation surveys. Roe on bottom, landing coluger on top of casing. RupBTD) at 6116'. Liner hand, 5358', 5274' and 5190' di 0.25 pps celloflake. Slof 50/50 Class H Poz with at 13.7 ppg to yield 1.3 e increased. Pack off line.	un logs. Run 60 joints lar one joint up, 9 - 4 n in hole on 3 1/2" ger at 3623' Cement with 90 sacks urry mixed at 12.3 ppg 2% gel, 5 pps gilsonite, 3 cf/sk. Good
		99111	
1218			
	ove is true and complete to the best of my knowledge and	i belief.	

TITLE

TYPE OR PRINT NAME R. E. Fielder

CONDITIONS OF APPROVAL, IF ANY

APPROVED BY

(This space for State U

DATE <u>11/13/01</u>

TELEPHONE NO. (505) 325-5220