V.

Form	9-3818
(Feb	. 1951)

l	X		
l		;	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Land Office	Hercico
Lease No	05/105
Unit	IW/4

	rate
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING.
HOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	·
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
IOTICE OF INTENTION TO ABANDON WELL	MY 6 1958
(INDICATE ABOVE BY CHECK MA	ARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	, 19, 19,
H111 ell No5 is located990 ft. fro	om. ${N \brace W}$ line and 1650. ft. from ${W \brack W}$ line of sec20
M/4 Sec. 20 24-North (1/4 Sec. and Sec. No.) (Twp.)	Range) (Meridian)
lo. Blanco P.C. Ext. Rio Ar	riba County, New Mexico.
(Field) (Count	ty or Subdivision) (State or Territory)
ne elevation of the derrick floor above sea	level is .6898 ft. 'AILS OF WORK
175.1	
tate names of and expected depths to objective sands; show	raises, weights, and lengths of proposed casings; indicate mudding jobs, cement- all other important proposed work)
tate names of and expected depths to objective sands; show	r sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-
tate names of and expected depths to objective sands; show ing points, and a	r sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- all other important proposed work)
ate names of and expected depths to objective sands; show ing points, and a	r sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- all other important proposed work)
ate names of and expected depths to objective sands; show ing points, and a sectored Cliffs and test. Estimaterized casing: 90° of 8-5/8° 24#	r sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work)
rate names of and expected depths to objective sands; show ing points, and a rictured Cliffs sand test. Estimateurface casing: 90' of 8-5/8" 24# roduction: Approximately 3200' o	raises, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) sted total depth 3200*. J-55 - cemented to surface.
ictured Cliffs and test. Estimaterface casing: 90' of 8-5/8" 24# roduction: Approximately 3200' of	raises, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) ated total depth 3200°. J-55 - cemented to surface. 2.5-1/2" OD 15.5# J-55 cemented with 100 sacks
ictured Cliffs send test. Estimaterface casing: 90' of 8-5/8" 24# roduction: Approximately 3200' of	raises, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) ated total depth 3200°. J-55 - cemented to surface. 2.5-1/2" OD 15.5# J-55 cemented with 100 sacks
ictured Cliffs and test. Estimateriace casing: 90' of 8-5/8" 24# roduction: Approximately 3200' of	raises, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) ated total depth 3200°. J-55 - cemented to surface. 2.5-1/2" OD 15.5# J-55 cemented with 100 sacks
ictured Cliffs and test. Estimateriace casing: 90' of 8-5/8" 24# roduction: Approximately 3200' of	raises, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) ated total depth 3200°. J-55 - cemented to surface. 2.5-1/2" OD 15.5# J-55 cemented with 100 sacks
letured Cliffs sand test. Estimaterface casing: 90' of 8-5/8" 24# reduction: Approximately 3200' of ster fractured.	raises, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) sted total depth 3200'. J-55 - cemented to surface. 2.5-1/2" OD 15.5- J-55 cemented with 100 sacks ated, the producing section will be sand
letured Cliffs sand test. Estimaterface casing: 90' of 8-5/8" 24# reduction: Approximately 3200' of commercial production is indicated fractured.	raises, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) ated total depth 3200°. J-55 - cemented to surface. 2.5-1/2" OD 15.5# J-55 cemented with 100 sacks
eletured Cliffs send test. Estimaterface casing: 90' of 8-5/8" 24# roduction: Approximately 3200' of 8-5/8" roduction is indicated fractured.	raises, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) sted total depth 3200'. J-55 - cemented to surface. 2.5-1/2" OD 15.5- J-55 cemented with 100 sacks ated, the producing section will be sand
ictured Cliffs and test. Estimaterface casing: 90' of 8-5/8" 24# roduction: Approximately 3200' of commercial production is indicated fractured. I understand that this plan of work must receive approva	raises, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) sted total depth 3200'. J-55 - cemented to surface. 2.5-1/2" OD 15.5- J-55 cemented with 100 sacks ated, the producing section will be sand
ictured Cliffs and test. Estimaterface casing: 90' of 8-5/8" 24# roduction: Approximately 3200' of services fractured.	raises, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) sted total depth 3200'. J-55 - cemented to surface. 2.5-1/2" OD 15.54 J-55 cemented with 100 sacks ated, the producing section will be sand
letured Cliffs and test. Estimateriace casing: 90' of 8-5/8" 24# reduction: Approximately 3200' of connercial production is indicated fractured. I understand that this plan of work must receive approvalences. Products: P. O. Box 726	raises, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) sted total depth 3200'. J-55 - cemented to surface. 2.5-1/2" OD 15.5- J-55 cemented with 100 sacks ated, the producing section will be sand
letured Cliffs and test. Estimaterface casing: 90° of 8-5/8° 24 reduction: Approximately 3200° of commercial production is indicated fractured.	raises, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) sted total depth 3200'. J-55 - cemented to surface. 2.5-1/2" OD 15.5- J-55 cemented with 100 sacks ated, the producing section will be sand
letured Cliffs and test. Estimateriace casing: 90' of 8-5/8" 24# reduction: Approximately 3200' of connercial production is indicated fractured. I understand that this plan of work must receive approvalences. Products: P. O. Box 726	raises, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) sted total depth 3200'. J-55 - cemented to surface. 2.5-1/2" OD 15.5- J-55 cemented with 100 sacks ated, the producing section will be sand

NEW MEXICO OIL CONSERVATION COMMISSION

Well Location and Acreage Dedication Plat

Section A.				Date August 6, 1958
Operator FRAN	K A. SCHULTZ		seHILL	
Well No. 5	_Unit Letter_C	Section 20	Township	24 NORTH Range WEST, NMPM
County RIO AR	reet from	Flevation 689	ne Dedicat	et From the WEST Line ed Acreage /60 Acres
Name of Produci	ng Formation Pla	stured Cliffs	Pool So	Blanco P. C. Ext.
1. Is the Oper	ator the only ow	vner* in the ded	icated acreage o	utlined on the plat below?
Yes		one is the H bas	e the intersets	of all the awners been
				of all the owners been es If answer is
"ves," Type	of Consolidation	on Communit	izati:n	
	er to question ·	two is "no," lis	t all the owners	and their respective interests
below:		Rel: ULD	hter dereg to be	Comber 191/
	Owner		Land Des	cription
				rail r
ection.B				
N.M. 02102	N.M.02703			7
Notic Uzique	Norto-Denue			This is to certify that the
	1 %		1	information in Section A
	1 %			above is true and complete
10-0'			1	to the best of my knowledge
/650	Ţ		· - I	and belief.
	 	 	 	Frank A. Schultz
Santa Pe	Santa Fe		!	(Operator))
079456	079456		1	X Sen / lax
	1		1	(Representative)
	1			C. Beeson Neal, Agent
	1		i	Box 728 - Farmington, N.M.
	· ·	20		Address
			000	This is to certify that the
			11/1/11	well location shown on the
	! 		1 14///20	plat in Section B was plotted
		$\int \int $	16 7/11	from field notes of actual
			0 7/0	surveys made by me or under
	 -	<u>+</u>	H-120-4	my supervision and that the same is true and correct to
	1		11: 50m /	the best of my knowledge and
	1			haliaf
				Date Surveyed 30 July 1958
				0. 700-
	i			Registered Professional
			ł	Engineer and/or Land Surveyor James P. Leese
				 1 9,25
330 660 990	1320 1650 1980 2310	2640 2000 150	00 1000 500	Certificate No

INSTRUCTIONS FOR COMPLETION:

- 1. Operator shall furnish and certify to the information called for in Section A.
- 2. Operator shall outline the dedicated acreage for both oil and gas wells on the plat in Section B.
- 3. A registered professional engineer or land surveyor registered in the State of New Mexico or approved by the Commission shall show on the plate the location of the well and certify this information in the space provided.
- 4. All distances shown on the plat must be from the outer boundaries of Section.
- 5. If additional space is needed for listing owners and their respective interests as required in question 3, Section A, please use space below

^{* &}quot;Owner" means the person who has the right to drill into and to produce from any pool and to appropriate the production either for himself or for himself and another. (65-3-29 (e) NMSA 1953 Comp.)