(SUBMIT IN TRIPLICATE)

Land Office Santa Fe

Unit .....

Lans No. SF 000715

## 30

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Monage	AND REPORTS ON WELLS	
NOTICE OF INTENTION TO DRILL	CUpers	
TOTAL OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF WATER SHUT-OFF	
MOTICE OF INTENTION TO TEST WATER SHIP OFF	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.	
MOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	REPURT OF ALTERING CASING	1 1
THE STOR TO SHOOT OR ACIDIZE	SOUSEQUENT REPORT OF RE-DRILLING OF PERAIR	
NOTICE OF INTENTION TO PULL OR ALTER CASING	REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO ABANDON WELL	SUPPLEMENTARY WELL HISTORY	*
(INDICATE ABOVE BY CHECK MAN	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
Sumico-Federal	July 2,	1044
Well No. 1		, 19.62
(4 Sec. and Sec. No.)  South Blaces, Picture (Twp.)	(Range) (Meridian)	FIVE
	io Arriba	LIT LU
	of Subdivision)	1000
he elevation of the deritek floor above sea lev	7607 c	1962
above sea lev	ver is the Diagonal fit.	N. COM.
DETAI	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
and expected depths to objective sands; show size	LS OF WORK	ST. 3
ing points, and all of	LS OF WORK  ss, weights, and lengths of proposed casings; indicate mudding isl	ST. 3
bject well spudded May 13, 1961. 8	LS OF WORK  ss, weights, and lengths of proposed casings; indicate mudding joint ther important proposed work)  5/8" Casing gat at QS;	be, cement-
bject well spudded May 13, 1961. 8 3481'. Top of Pictured Cliffs, 33	LS OF WORK  ss, weights, and lengths of proposed casings; indicate mudding joint ther important proposed work)  5/8" casing set at 95', cemented w/:  86'. 4 1/2" - 9.55 casing set at 9.55	be, coment-
bject well spudded May 13, 1961. 8 3481'. Top of Pictured Cliffs, 33 mented w/75 sacks. Electric log top	LS OF WORK  ss, weights, and lengths of proposed casings; indicate mudding joint ther important proposed work)  5/8" casing set at 95', cemented w/:  86'. 4 1/2" - 9.5# casing set at 34';  ps, Kirtland, 3200'. Freed lend	be, cement.  50 sacks. 75',
bject well spudded May 13, 1961. 8 3481'. Top of Pictured Cliffs, 33 mented w/75 sacks. Electric log top	LS OF WORK  ss, weights, and lengths of proposed casings; indicate mudding joint ther important proposed work)  5/8" casing set at 95', cemented w/:  86'. 4 1/2" - 9.5# casing set at 34';  ps, Kirtland, 3200'. Freed lend	be, cement 50 sacks
bject well spudded May 13, 1961. 8 3481'. Top of Pictured Cliffs, 33 mented w/75 sacks. Electric log top presently awaiting completion rig. 62-92 on 5/3/62. Cement drilled out	LS OF WORK  st, weights, and lengths of proposed casings; indicate mudding joing their important proposed work)  5/8" casing set at 95', cemented w/:  86'. 4 1/2" - 9.5# casing set at 34;  ps, Kirtland, 3200'; Fruitland, 3335'  Subject well squessed w/100 sacks of to 3455', well performed 3200';	50 sacks. 75', Well
bject well spudded May 13, 1961. 8 3481'. Top of Pictured Cliffs, 33 mented w/75 sacks. Electric log top presently swaiting completion rig. 62-92 on 5/3/62. Gement drilled out r foot. Fraced 5/6/62 with 30,000#	LS OF WORK  ss, weights, and lengths of proposed casings; indicate mudding join ther important proposed work)  5/8" casing set at 95', cemented w/3  86'. 4 1/2" - 9.5# casing set at 34'  ps, Kirtland, 3200'; Fruitland, 3335'  Subject well squeezed w/100 sacks of to 3455'. Well perforated 3389-340  20-40 mesh sand, 40.800 calless	50 sacks. 75', Well
bject well spudded May 13, 1961. 8 3481'. Top of Pictured Cliffs, 33 mented w/75 sacks. Electric log top presently swaiting completion rig. 62-92 on 5/3/62. Gement drilled out r foot. Fraced 5/6/62 with 30,000#	LS OF WORK  ss, weights, and lengths of proposed casings; indicate mudding join ther important proposed work)  5/8" casing set at 95', cemented w/3  86'. 4 1/2" - 9.5# casing set at 34'  ps, Kirtland, 3200'; Fruitland, 3335'  Subject well squeezed w/100 sacks of to 3455'. Well perforated 3389-340  20-40 mesh sand, 40.800 calless	50 sacks. 75', Well
bject well spudded May 13, 1961. 8 3481'. Top of Pictured Cliffs, 33 mented w/75 sacks. Electric log top presently swaiting completion rig. 62-92 on 5/3/62. Gement drilled out r foot. Fraced 5/6/62 with 30,000#	LS OF WORK  ss, weights, and lengths of proposed casings; indicate mudding join ther important proposed work)  5/8" casing set at 95', cemented w/3  86'. 4 1/2" - 9.5# casing set at 34'  ps, Kirtland, 3200'; Fruitland, 3335'  Subject well squeezed w/100 sacks of to 3455'. Well perforated 3389-340  20-40 mesh sand, 40.800 calless	50 sacks. 75', Well
bject well spudded May 13, 1961. 8 3481'. Top of Pictured Cliffs, 33; mented w/75 sacks. Electric log top presently swaiting completion rig. 62-92 on 5/3/62. Cement drilled out r foot. Fraced 5/6/62 with 30,000#	LS OF WORK  ss, weights, and lengths of proposed casings; indicate mudding join ther important proposed work)  5/8" casing set at 95', cemented w/3  86'. 4 1/2" - 9.5# casing set at 34'  ps, Kirtland, 3200'; Fruitland, 3335'  Subject well squeezed w/100 sacks of to 3455'. Well perforated 3389-340  20-40 mesh sand, 40.800 calless	50 sacks. 75', Well
bject well spudded May 13, 1961. 8 3481'. Top of Pictured Cliffs, 33; mented w/75 sacks. Electric log top presently swaiting completion rig. 62-92 on 5/3/62. Cement drilled out r foot. Fraced 5/6/62 with 30,000#	LS OF WORK  ss, weights, and lengths of proposed casings; indicate mudding join ther important proposed work)  5/8" casing set at 95', cemented w/3  86'. 4 1/2" - 9.5# casing set at 34'  ps, Kirtland, 3200'; Fruitland, 3335'  Subject well squeezed w/100 sacks of to 3455'. Well perforated 3389-340  20-40 mesh sand, 40.800 calless	50 sacks. 75', Well
bject well spudded May 13, 1961. 8 3481'. Top of Pictured Cliffs, 33 mented w/75 sacks. Electric log top presently swaiting completion rig. 62-92 on 5/3/62. Gement drilled out r foot. Fraced 5/6/62 with 30,000#	LS OF WORK  ss, weights, and lengths of proposed casings; indicate mudding join ther important proposed work)  5/8" casing set at 95', cemented w/3  86'. 4 1/2" - 9.5# casing set at 34'  ps, Kirtland, 3200'; Fruitland, 3335'  Subject well squeezed w/100 sacks of to 3455'. Well perforated 3389-340  20-40 mesh sand, 40.800 calless	50 sacks. 75', Well
bject well spudded May 13, 1961. 8 3481'. Top of Pictured Cliffs, 33 mented w/75 sacks. Electric log top presently awaiting completion rig. 62-92 on 5/3/62. Cement drilled out	LS OF WORK  ss, weights, and lengths of proposed casings; indicate mudding join ther important proposed work)  5/8" casing set at 95', cemented w/3  86'. 4 1/2" - 9.5# casing set at 34'  ps, Kirtland, 3200'; Fruitland, 3335'  Subject well squeezed w/100 sacks of to 3455'. Well perforated 3389-340  20-40 mesh sand, 40.800 calless	50 sacks. 75', Well
bject well spudded May 13, 1961. 8 3481'. Top of Pictured Cliffs, 33; mented w/75 sacks. Electric log top presently swaiting completion rig. 62-92 on 5/3/62. Gement drilled out r foot. Fraced 5/6/62 with 30,000# sm pressure 1300 PSI, Treatment pres 1" tubing to 3380'. Cleaning well	LS OF WORK  ss, weights, and lengths of proposed casings; indicate mudding joint their important proposed work)  5/8" casing set at 95', cemented w/3 86'. 4 1/2" - 9.5# casing set at 34' ps, Kirtland, 3200'; Fruitland, 3335' Subject well squeezed w/100 sacks of to 3455'. Well perforated 3389-340' 20-40 mesh sand, 40,800 gallons water source 2000 PSI. Injection rate 37.6' Lup to run Back Pressure Test	50 sacks. 75', Well
bject well spudded May 13, 1961. 8 3481'. Top of Pictured Cliffs, 33; mented w/75 sacks. Electric log top presently swaiting completion rig. 62-92 on 5/3/62. Gement drilled out r foot. Fraced 5/6/62 with 30,000# swn pressure 1300 PSI, Treatment pres 1" tubing to 3380'. Cleaning well	LS OF WORK  ss, weights, and lengths of proposed casings; indicate mudding joint their important proposed work)  5/8" casing set at 95', cemented w/3 86'. 4 1/2" - 9.5# casing set at 34' ps, Kirtland, 3200'; Fruitland, 3335' Subject well squeezed w/100 sacks of to 3455'. Well perforated 3389-340' 20-40 mesh sand, 40,800 gallons water source 2000 PSI. Injection rate 37.6' Lup to run Back Pressure Test	50 sacks. 75', Well cement 01, 4 shoter. Break
bject well spudded May 13, 1961. 8 3481'. Top of Pictured Cliffs, 33; mented w/75 sacks. Electric log top presently swaiting completion rig. 62-92 on 5/3/62. Gement drilled out r foot. Fraced 5/6/62 with 30,000# wen pressure 1300 PSI, Treatment pres a 1" tubing to 3380'. Cleaning well	LS OF WORK  st, weights, and lengths of proposed casings; indicate mudding joing their important proposed work)  5/8" casing set at 95', cemented w/:  86'. 4 1/2" - 9.5# casing set at 34;  ps, Kirtland, 3200'; Fruitland, 3335'  Subject well squeezed w/100 sacks of to 3455'. Well perforated 3389-340;  20-40 mesh sand, 40,800 gallons water source 2000 PSI. Injection rate 37.6;  I up to run Back Pressure Test  atter	50 sacks. 75', Well cement 01, 4 shoter. Break
bject well spudded May 13, 1961. 8 3481'. Top of Pictured Cliffs, 33; mented w/75 sacks. Electric log top presently swaiting completion rig. 62-92 on 5/3/62. Gement drilled out r foot. Fraced 5/6/62 with 30,000f sm pressure 1300 PSI, Treatment pres a 1" tubing to 3380'. Cleaning well understand that this plan of work must receive approval in wri apany  E. L. FUNDINGSLAND  1402 Denver U.S. National Cen	LS OF WORK  st, weights, and lengths of proposed casings; indicate mudding joing their important proposed work)  5/8" casing set at 95', cemented w/:  86'. 4 1/2" - 9.5# casing set at 34;  ps, Kirtland, 3200'; Fruitland, 3335'  Subject well squeezed w/100 sacks of to 3455'. Well perforated 3389-340;  20-40 mesh sand, 40,800 gallons water source 2000 PSI. Injection rate 37.6;  I up to run Back Pressure Test	50 sacks. 75', Well cement 01, 4 shoter. Break
bject well spudded May 13, 1961. 8 3481'. Top of Pictured Cliffs, 33; mented w/75 sacks. Electric log top presently swaiting completion rig. 62-92 on 5/3/62. General drilled out r foot. Fraced 5/6/62 with 30,000* sm pressure 1300 PSI, Treatment pres 11" tubing to 3380'. Cleaning well understand that this plan of work must receive approval in wri	LS OF WORK  st, weights, and lengths of proposed casings; indicate mudding joing their important proposed work)  5/8" casing set at 95', cemented w/:  86'. 4 1/2" - 9.5# casing set at 34;  ps, Kirtland, 3200'; Fruitland, 3335'  Subject well squeezed w/100 sacks of to 3455'. Well perforated 3389-340;  20-40 mesh sand, 40,800 gallons water source 2000 PSI. Injection rate 37.6;  I up to run Back Pressure Test  atter	50 sacks. 75', Well cement 01, 4 shoter. Break
bject well spudded May 13, 1961. 8 3481'. Top of Pictured Cliffs, 33; mented w/75 sacks. Electric log top presently awaiting completion rig. 52-92 on 5/3/62. Cement drilled out r foot. Fraced 5/6/62 with 30,000f m pressure 1300 PSI, Treatment pres 11" tubing to 3380'. Cleaning well the completion of	LS OF WORK  st, weights, and lengths of proposed casings; indicate mudding joing their important proposed work)  5/8" casing set at 95', cemented w/:  86'. 4 1/2" - 9.5# casing set at 34;  ps, Kirtland, 3200'; Fruitland, 3335'  Subject well squeezed w/100 sacks of to 3455'. Well perforated 3389-340;  20-40 mesh sand, 40,800 gallons water source 2000 PSI. Injection rate 37.6;  I up to run Back Pressure Test  atter	50 sacks. 75', Well cement 01, 4 shoter. Break
bject well spudded May 13, 1961. 8 3481'. Top of Pictured Cliffs, 33; mented w/75 sacks. Electric log top presently swaiting completion rig. 52-92 on 5/3/62. Cement drilled out r foot. Fraced 5/6/62 with 30,000f on pressure 1300 PSI, Treatment pres 11" tubing to 3380'. Cleaning well apany E. L. FUNDINGSLAND 1402 Denver U.S. National Cen	LS OF WORK  st, weights, and lengths of proposed casings; indicate mudding joing their important proposed work)  5/8" casing set at 95', cemented w/:  86'. 4 1/2" - 9.5# casing set at 34;  ps, Kirtland, 3200'; Fruitland, 3335'  Subject well squeezed w/100 sacks of to 3455'. Well perforated 3389-340;  20-40 mesh sand, 40,800 gallons water source 2000 PSI. Injection rate 37.6;  I up to run Back Pressure Test  atter	50 sacks. 75', Well cement 01, 4 shoter. Break