Foi	rm 9 Feb. 1	-881: 961)	B.	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Sante Pe
Lease No.	078925
Unit Canyo	n Lergo

SUNDRY N	OTICES AND	REPORTS ON WELLS	
NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	· S	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SH	HUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR R	REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIE	DIZEs	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER	CASINGS	UPPLEMENTARY WELL HISTORY	·
NOTICE OF INTENTION TO ABANDON WELL		Water Frac.	
(INDICATE ABO	OVE BY CHECK MARK NATUR	E OF REPORT, NOTICE, OR OTHER DATA)	
		Nay 24	10
/ell No is located	990 (N)		, 17
in located	it. from	line andft. from W line of sec	•
W./4 Sec. 26 (% Sec. and Sec. No.)	24 H 6 V	Y.M.P.M.	
llard Pictured Cliffs	(Twp.) (Range) Ric Arriba	(Bididian)	
(Field)	(County or Subdivi	New Mexico	
		(State or Territory)	
te names of and avacated doubles and a			
ate names of and expected depths to object ii	tive sands; show sizes, weigh ng points, and all other imp	ts, and lengths of proposed casings; indicate mudding jo ortant proposed work)	bs, cen
4-60 Total Depth 234 ter fractured Pictured C 92-96 w/2 SFF with 17,2 7 # WG-3/1000 # gal. an	9. C.O. Total liffs perforated 60 gallons water d 10,000 # sand.	Depth 2341. intervals 2248-54; 2268-74;	
ter fractured Pictured C 92-96 w/2 SFF with 17,2 7 # WG-3/1000 # gal., and k. pr. 3400 #, avg. tr.; pyped total of 6 balls in	9. C.O. Total liffs perforated 60 gallons water d 10,000 f sand. pr. 2800 f. I.B n 3 stages.	Depth 2341. I intervals 2248-54; 2268-74; with 1 \$ Calcium Chloride Breakdown pr. 2700 \$. 1. 18 bbls./min. Flush 846-81.	
ter fractured Pictured C 92-96 w/2 SFF with 17,2 7 # WG-3/1000 # gal., and x. pr. 3400 #, avg. tr.; opped total of 6 balls in	9. C.O. Total liffs perforated 60 gallons water d 10,000 f sand. pr. 2800 f. I.B n 3 stages.	Depth 2341. I intervals 2248-54; 2268-74; with 1 \$ Calcium Chloride Breakdown pr. 2700 \$. 1. 18 bbls./min. Flush 846-81. RECEIVED MAY 2 7 1960	
ter fractured Pictured C 22-96 w/2 SFF with 17,2 7 # WG-3/1000 # gal., and t. pr. 3400 #, avg. tr. p opped total of 6 balls in	9. C.O. Total liffs perforated 60 gallons water d 10,000 # sand. pr. 2800 #. I.B n 3 stages.	Depth 2341. I intervals 2248-54; 2268-74; with 1 \$ Calcium Chloride Breakdown pr. 2700 \$. 1. 18 bbls./min. Flush 846-81. RECEIVED MAY 2 7 1960	