\*

## (SUBMIT IN TRIPLICATE)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Budget Bureau Vo. 42-R250.4. Approval expires 12-31-60.
Jicarilla Tribal
Allottee

Lease No. Jicarilla Tribal Contract 146

## CORRECTED REPORT

	S AND REPORTS ON WELLS
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ASTOIZED IN
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OF REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	
NOTICE OF INTENTION TO PULL OR ALTER CASING.	subsequent report of abandonment NOV 20 1962
NOTICE OF INTENTION TO ABANDON WELL	11101VI 10000000000000000000000000000000
	U. S. GEOLOGICAL SURV
(Indicate above by Check M	MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) FARMINGTON, NEW MEX
Jicarilla Contract 146	Farmington, New Mexico Movember 19, 19 62
vell No. 15 is located 940 ft.	from S line and 1450 ft. from W line of sec. 9
E/L SW/L Section 9 T-251 (14 Sec. and Sec. No.) (Twp.)	R-91 N.M.P.M. (Range) (Meridian)
Otero Checra Rio Arrib	· · · · · · · · · · · · · · · · · · ·
/707 3 34	ounty or Subdivision) (State or Territory)
	TAILS OF WORK w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-
he above well was spudded on Oct 10° and 8-5/8" casing set at the containing 25 calcium chloride. In community tested casing with 500	TAILS OF WORK  we sizes, weights, and lengths of proposed casings; indicate mudding jobs, comental other important proposed work)  sober 27, 1962. Hole was drilled to a depth of it depth with 135 sacks of neat Incor coment.  Coment circulated to surface. After waiting pounds. Test o.k. Reduced hole to 7-7/8* at
the above well was spudded on Oct.  The above well was spudded on Oct.  10' and 8-5/8" casing set at the containing 25 calcium chloride. It is coment, tested easing with 500 lo' and resumed drilling.	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work)  sober 27, 1962. Hole was drilled to a depth of it depth with 135 sacks of next Incor commut. Cement circulated to surface. After waiting pounds. Test o.k. Reduced hole to 7-7/8" at correct spudding date and also to report
he above well was spudded on Oct 10° and 8-5/8" casing set at the containing 25 calcium chloride. In sement, tested casing with 500 10° and resumed drilling.	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work)  sober 27, 1962. Hole was drilled to a depth of it depth with 135 sacks of next Incor commut.  Coment circulated to surface. After waiting pounds. Test o.k. Reduced hole to 7-7/8" at  correct spudding date and also to report
he above well was spudded on Oct.  he above well was spudded on Oct.  10' and 8-5/8" casing set at the outsiming 25 calcium chloride. In coment, tested casing with 500 lo' and resumed drilling.  Perceted Report filed to report correct (RDB) elevations.	we sizes, weights, and lengths of proposed casings; indicate mudding jobs, comental other important proposed work)  sober 27, 1962. Hole was drilled to a depth of it depth with 135 sasks of next Incor comment.  Coment circulated to surface. After waiting pounds. Test o.k. Reduced hole to 7-7/8" at  correct spudding date and also to report
he above well was spudded on Oct.  10° and 8-5/8" caming set at the containing 25 calcium chloride.  In commut, tested casing with 500 lo° and resumed drilling.	we sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work)  sober 27, 1962. Hole was drilled to a depth of it depth with 135 sacks of next Incor commut. Cement circulated to surface. After waiting pounds. Test o.k. Reduced hole to 7-7/8" at cerrect spudding date and also to report.  Convert spudding date and also to report.  RPORATION
he above well was spudded on Oct.  10° and 8-5/8° casing set at the containing 25 calcium chloride.  In community, tested casing with 500 lo° and resumed drilling.  25 percent (RDB) elevation.	we sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work)  sober 27, 1962. Hole was drilled to a depth of it depth with 135 sacks of next Incor communication of the circulated to surface. After waiting pounds. Test o.k. Reduced hole to 7-7/8" at cerrect spudding date and also to report  correct spudding date and also to report  CRIGINAL SIGNED BY